

PRODUCT SPECIFICATION SHEET

Product Name: Altinex® AnyWire™ HDMI Extender

Features / Description		TP315-101
Input Connectors		
Digital Video + Audio		HDMI F, Type A (1)
AC Power		C7 M (1)
Output Connectors		
Digital Video + Audio		HDMI F, Type A (1)
Anywire Video		Terminal Post F (2)
IR (from receiver side)		3.5 mm Audio F (1)
Compatibility		
Signal types		HDMI
Signal resolution		HD Resolutions up to 1080p
Accessories Included		
HDMI Cable		
AC Power Cord, NEMA 1-15P to IEC C7		
IR Emitter		
Mechanical		
Material		Aluminum
Color		Black
Height		1.05 in (27 mm)
Width		6.73 in (171 mm)
Depth		3.51 in (89 mm)
Weight		1.0 lbs. (0.45 kg)
T° Operating		10°C-45°C
Humidity		90% non-condensing
MTBF (calc.)		38,000 hrs.
Electrical		
Video Input Signals		
Digital Video + Audio		HDMI Standard

Features / Description	TP315-101
Video Output Signals	
Digital Video + Audio	Anywire
Power	
100~240 VAC	7 X Max
	100 VAC at 70 mA
	240 VAC at 30 mA

Features / Description	TP315-102
Input Connectors	
Digital Video + Audio	Terminal Post F (2)
AC Power	C7 M (1)
IR Receiver (3.5mm Audio F (1)	
Output Connectors	HDMI F, Type A (1)
Digital Video + Audio	HDMI F, Type A (1)
Compatibility	
Signal types	HDMI
Signal resolution	HD Resolutions up to 1080p
Accessories Included	
HDMI Cable	
AC Power Cord, NEMA 1-15P to IEC C7	
IR Emitter	
Mechanical	
Material	Aluminum
Color	Black
Height	1.05 in (27 mm)
Width	6.73 in (171 mm)
Depth	3.51 in (89 mm)
Weight	1.0 lbs. (0.45 kg)
T° Operating	10°C-45°C
Humidity	90% non-condensing
MTBF (calc.)	38,000 hrs.

Features / Description		TP315-102	
Electrical			
Video Input Signals			
Digital Video + Audio		Anywaire	
Video Output Signals			
Digital Video + Audio		HDMI Standard	
Power			
100~240 VAC		7 X Max	
		100 VAC at 70 mA	
		240 VAC at 30 mA	