

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Standard Cable Ties

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T18S0C2	Cable Tie, 3.3" Long, UL Rated	18lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 0.63	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL ANSI/UL 62275 UL csa-C22.2 no. 62275
HT-T18S0M4	Cable Tie, 3.3" Long, UL Rated	18lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 0.63	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL ANSI/UL 62275 UL csa-C22.2 no. 62275
HT-T18S9C2	Cable Tie, 3.3" Long, UL Rated	18lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 0.63	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL csa-C22.2 no. 62275 UL ANSI/UL 62275
HT-T18S9M4	Cable Tie, 3.3" Long, UL Rated	18lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 0.63	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL csa-C22.2 no. 62275 UL ANSI/UL 62275
HT-T18R0C2	Cable Tie, 4" Long, UL Rated	18lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 0.87	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18R0M4	Cable Tie, 4" Long, UL Rated	18lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 0.87	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18R0PPC2	Cable Tie, 4" Long	8lb Tensile Strength	PP, Black, 100/pkg	0.06 - 0.75	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	Yes	-
HT-T18R10M4	Cable Tie, 4" Long, UL Rated	18lb Tensile Strength	PA66, White, 1000/pkg	0.06 - 0.87	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18R9C2	Cable Tie, 4" Long, UL Rated	18lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 0.87	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T18R9M4	Cable Tie, 4" Long, UL Rated	18lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 0.87	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T18R9PPM4	Cable Tie, 4" Long	8lb Tensile Strength	PP, Natural, 1000/pkg	0.06 - 0.75	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	Yes	-
HT-T18I0C2	Cable Tie, 5.5" Long, UL Rated	18lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T18I0M4	Cable Tie, 5.5" Long, UL Rated	18lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18I3M4	Cable Tie, 5.5" Long, UL Rated	18lb Tensile Strength	PA66, Orange, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18I4M4	Cable Tie, 5.5" Long, UL Rated	18lb Tensile Strength	PA66, Yellow, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18I9C2	Cable Tie, 5.5" Long, UL Rated	18lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T18I9M4	Cable Tie, 5.5" Long, UL Rated	18lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T30R0C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R0M4	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R10C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, White, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R10M4	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, White, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R1C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Brown, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T30R2C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Red, 100/ pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R3C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Orange, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R4C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Yellow, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R4M4	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Yellow, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R5C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Green, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R5M4	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Green, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R6C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Blue, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R7C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Purple, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R8C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Gray, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30R9C2	Cable Tie, 6" Long, UL Rated	30lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T30R9PPC2	Cable Tie, 6" Long	20lb Tensile Strength	PP, Natu- ral, 100/ pkg	0.31 - 1.26	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	Yes	-
HT-T50S0C2	Cable Tie, 6" Long, UL Rated	50lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T50S0M4	Cable Tie, 6" Long, UL Rated	50lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50S9C2	Cable Tie, 6" Long, UL Rated	50lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50S9M4	Cable Tie, 6" Long, UL Rated	50lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18L0C2	Cable Tie, 8" Long, UL Rated	18lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18L0M4	Cable Tie, 8" Long, UL Rated	18lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18L2M4	Cable Tie, 8" Long, UL Rated	18lb Tensile Strength	PA66, Red, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18L4M4	Cable Tie, 8" Long, UL Rated	18lb Tensile Strength	PA66, Yellow, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18L9C2	Cable Tie, 8" Long, UL Rated	18lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T18L9M4	Cable Tie, 8" Long, UL Rated	18lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R0PPC2	Cable Tie, 8" Long	25lb Tensile Strength	PP, Black, 100/pkg	0.50 - 1.75	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	Yes	-
HT-T50R0PPM4	Cable Tie, 8" Long, UL Rated	25lb Tensile Strength	PP, Black, 1000/pkg	0.50 - 1.75	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	Yes	-
HT-T50R9PPC2	Cable Tie, 8" Long, UL Rated	25lb Tensile Strength	PP, Natu- ral, 100/ pkg	0.50 - 1.75	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	Yes	-
HT-T30L0C2	Cable Tie, 8" Long, UL Rated	30lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T30L3M4	Cable Tie, 8" Long, UL Rated	30lb Tensile Strength	PA66, Orange, 1000/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30L9C2	Cable Tie, 8" Long, UL Rated	30lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30L9M4	Cable Tie, 8" Long, UL Rated	30lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40R0C2	Cable Tie, 8" Long, UL Rated	40lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40R0M4	Cable Tie, 8" Long, UL Rated	40lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40R10M4	Cable Tie, 8" Long, UL Rated	40lb Tensile Strength	PA66, White, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40R9C2	Cable Tie, 8" Long, UL Rated	40lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T40R9M4	Cable Tie, 8" Long, UL Rated	40lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R0C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R0M4	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R10C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, White, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R10M4	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, White, 1000/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T50R1C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Brown, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R2C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Red, 100/ pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R2M4UL	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Red, 1000/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R3C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Orange, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R4C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Yellow, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R5C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Green, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R6C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Blue, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R7C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Purple, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R8C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Gray, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50R9C2	Cable Tie, 8" Long, UL Rated	50lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T30LL0C2	Cable Tie, 11" Long, UL Rated	30lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30LL0M4	Cable Tie, 11" Long, UL Rated	30lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T30LL9C2	Cable Tie, 11" Long, UL Rated	30lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30LL9M4	Cable Tie, 11" Long, UL Rated	30lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40I0C2	Cable Tie, 11" Long, UL Rated	40lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40I0M4	Cable Tie, 11" Long, UL Rated	40lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40I9C2	Cable Tie, 11" Long, UL Rated	40lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40I9M4	Cable Tie, 11" Long, UL Rated	40lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50I0C2	Cable Tie, 12" Long, UL Rated	50lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50I0M4	Cable Tie, 12" Long, UL Rated	50lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50I2M4UL	Cable Tie, 12" Long, UL Rated	50lb Tensile Strength	PA66, Red, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50I7C2	Cable Tie, 12" Long, UL Rated	50lb Tensile Strength	PA66, Purple, 100/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50I9C2	Cable Tie, 12" Long, UL Rated	50lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T50I9M4	Cable Tie, 12" Long, UL Rated	50lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T30XL0C2	Cable Tie, 14" Long, UL Rated	30lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T30XL0M4	Cable Tie, 14" Long, UL Rated	30lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T30XL9C2	Cable Tie, 14" Long, UL Rated	30lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T30XL9M4	Cable Tie, 14" Long, UL Rated	30lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40L0C2	Cable Tie, 14" Long, UL Rated	40lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40L0M4	Cable Tie, 14" Long, UL Rated	40lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40L9C2	Cable Tie, 14" Long, UL Rated	40lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T40L9M4	Cable Tie, 14" Long, UL Rated	40lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L0C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Black, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L0M4	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Black, 1000/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L10C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, White, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L10M4	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, White, 1000/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T50L1C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Brown, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L2C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Red, 100/ pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L9C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Natural, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes	UL 62275
HT-T50L9M4	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Natural, 1000/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L2UVM4	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66UV, Red, 1000/pkg	0.06 - 4.33	UL 94 V-2	Yes	-40°F to +185°F (-40°C to +85°C)	No	UL-ZODZ2. E64139
HT-T50L3C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Orange, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L4C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Yellow, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L5C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Green, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L6C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Blue, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L7C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Purple, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275
HT-T50L8C2	Cable Tie, 15" Long, UL Rated	50lb Tensile Strength	PA66, Gray, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No	UL 62275

Part #	Dimensions	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)	Certs & Specs
HT-T120R0PPH4	Cable Tie, 15" Long, UL Rated	60lb Tensile Strength	PP, Black, 500/pkg	0.50 - 4.13	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	Yes	-
HT-T120R0PPK2	Cable Tie, 15" Long, UL Rated	60lb Tensile Strength	PP, Black, 50/pkg	0.50 - 4.13	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	No	-