

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® 1-Piece Cable Ties w/ Fir Tree Mount

Part #	Strength (Imperial)	Dimensions (L x W)	Fixation Method	Mounting Hole Dia. (Metric)	Disc Dia. (Imperial)	Flammability	Operating Temp.	Material, Color	UV Resistant	Reach Compliant (Art. 33)
HT-150-55610	18	4.3"L x 0.1"W	Fir tree for round holes	4.9 - 5.1 mm	0.5	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	PA66, Black	No	Yes
HT-157-00306	50	8.6"L x 0.18"W	Fir tree	6.1 - 6.9 mm	0.63	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	No
HT-155-05800	50	6.0"L x 0.19"W	Fir tree for round holes	6.5 - 7.0 mm	0.63	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHS, Black	No	Yes
HT-157-00050	50	6.5"L x 0.2"W	Fir tree	6.5 - 7.2 mm	0.63	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black, 500/pkg	No	No
HT-157-00376	50	6.3"L x 0.18"W	Fir tree	6.3 - 7.0 mm	0.63	UL 94 HB	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	No
HT-157-00355	50	6.6"L x 0.18"W	Fir tree	6.1 - 6.9 mm	0.63	UL 94 V-2	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Natural	No	Yes
HT-157-00308	50	6.3"L x 0.18"W	Fir tree	6.3 - 7.0 mm	0.63	UL 94 HB	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	Yes
HT-157-00296	50	6.6"L x 0.18"W	Fir tree for round holes	6.5 mm 6.35 mm (hexagonal)	0.63	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	PA6HIRHSUV, Black	No	Yes
HT-157-00373	50	6.6"L x 0.18"W	Fir Tree	6.5 mm (+/- 0.4 mm)	0.63	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	No	Yes
HT-157-00303	50	6.6"L x 0.18"W	Fir Tree	6.5 mm 6.35 mm (hexagonal)	0.63	UL 94 HB	-40°F to +257°F (-40°C to +125°C)	PA66HS, Gray	No	Yes
HT-157-00017	30	6.7"L x 0.21"W	Fir tree for round holes	6.8 - 7.2 mm	0.63	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	PA66, Black	No	No
HT-157-00287	50	6.5"L x 0.18"W	Fir tree	6.3 - 7.0 mm	0.63	UL 94 HB	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black, 4000/carton	No	No
HT-157-00115	50	6.4"L x 0.18"W	Fir tree for round holes	8.0 - 8.5 mm	0.63	-	-40°F to +266°F (-40°C to +130°C)	PA46, Gray	No	Yes
HT-157-00072	50	6.4"L x 0.18"W	Fir tree for round holes	8.0 - 8.5 mm	0.63	-	-40°F to +221°F (-40°C to +105°C)	PA66HS, Black	No	Yes

Part #	Strength (Imperial)	Dimensions (L x W)	Fixation Method	Mounting Hole Dia. (Metric)	Disc Dia. (Imperial)	Flammability	Operating Temp.	Material, Color	UV Resistant	Reach Com- pliant (Art. 33)
HT-157-00180	50	7.1"L x .20"W	Fir tree for oval holes	6.2 x 12.2 mm	0.63 x 1.02	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	PA66, natural	No	No
HT-157-00386	50	7.1"L x .20"W	Fir tree for oval holes	7.0 x 12.0 mm	0.63 x 0.83	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	PA66, Black	No	No
HT-157-00054	50	8.5"L x .2"W	Fir tree for oval holes	7.0 x 12.0 mm	0.60 x 0.80	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	Yes
HT-157-00052	50	8.5"L x .2"W	Fir tree	6.5 - 7.2 mm	0.63	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	Yes
HT-157-00302	50	6.5"L x 0.18"W	Fir tree	6.3 - 7.0 mm	0.63	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00323	50	9"L x 0.18"W	Fir tree for oval holes	6.5 x 13.0 mm 7.0 x 12.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00247	50	9"L x 0.18"W	Fir tree for oval holes	6.5 x 13.0 mm 7.0 x 12.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00370	50	6.6"L x .20"W	Fir tree for oval holes	6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm	0.69 x 0.93	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	No
HT-157-00371	50	6.62"L x .20"W	Fir tree for oval holes	7.0 x 12.0 mm 6.5 x 12.5 mm 6.5 x 13.0 mm 6.2 x 12.2 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	No
HT-157-00337	50	7.1"L x .20"W	Fir tree for oval holes	6.5 x 13.0 mm	0.63 x 0.83	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	PA66HS, Gray	No	No
HT-157-00388	50	6.5"L x .18"W	Fir tree for oval holes	6.5 x 13.0 mm	0.63 x 0.83	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	No
HT-157-00112	50	8"L x .20"W	Fir tree for round holes	M6	0.31	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00144	50	8"L x .2"W	Fir tree	M6	0.66	UL 94 HB	-40°F to +266°F (-40°C to +130°C)	PA46, Brown	No	Yes
HT-T50RTM- 250HSM4	50	8"L x 0.18"W	Fir tree for round holes	6.2 - 7.0 mm	0.5	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	No
HT-T50RTM- 250HSC2	50	8"L x 0.18"W	Fir tree for round holes	6.2 - 7.0 mm	0.5	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	Yes

Part #	Strength (Imperial)	Dimensions (L x W)	Fixation Method	Mounting Hole Dia. (Metric)	Disc Dia. (Imperial)	Flammability	Operating Temp.	Material, Color	UV Resistant	Reach Com- pliant (Art. 33)
HT-157-00073	50	8.3"L x 0.19"W	Fir tree	6.25 - 7.0 mm	0.5	UL 94 HB	-40°F to +212°F (-40°C to +100°C)	PA66HIRHS, Black	No	No
HT-T50RT- M25E8HM4	50	8"L x 0.19"W	Fir tree	6.35 - 7.0 mm	0.5	UL 94 HB	-40°F to +212°F (-40°C to +100°C)	PA66HIRHS, Gray	No	No
HT-T50RT- M25E0HSM4	50	8.3"L x 0.18"W	Fir tree	6.25 - 7.0 mm	0.5	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	Yes