

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Acrylic Adhesive Cable Tie Mount

Part #	Dimensions	Material, Color, Qty.	Cable Tie Width Max	Mounting Hole Dia. (Imperial)	Adhesive	Adhesive Temp.	Flammability	Operating Temp.	UV Resistant	Reach Compliant (Art. 33)
HT-MB3A0A2H4	0.75" x 0.75"	PA66, Black, 500/pkg	0.14	0.12	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB3A10A2C2	0.75" x 0.75"	PA66, White, 100/pkg	0.14	0.12	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB3A10A2H4	0.75" x 0.75"	PA66, White, 500/pkg	0.14	0.12	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4A0A2H4	1.12" x 1.12"	PA66, Black, 500/pkg	0.18	0.18	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4A10A2C2	1.12" x 1.12"	PA66, White, 100/pkg	0.18	0.18	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4A10A2H4	1.12" x 1.12"	PA66, White, 500/pkg	0.18	0.18	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB5A0A2F4	1.49" x 1.49"	PA66, Black, 250/pkg	0.35	0.19	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB5A10A2F4	1.49" x 1.49"	PA66, White, 250/pkg	0.35	0.19	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-151-01629	0.75" x 0.75"	PA66HIRH-SUV, Black, 100/pkg	0.14	0.12	Acrylic foam	-40°F to +176°F (-40°C to +80°C)	UL 94 HB (excluding adhesive)	-40°F to +221°F (-40°C to +105°C)	Yes	No
HT-151-01630	0.75" x 0.75"	PA66HIRH-SUV, Black, 500/pkg	0.14	0.12	Acrylic foam	-40°F to +176°F (-40°C to +80°C)	UL 94 HB (excluding adhesive)	-40°F to +221°F (-40°C to +105°C)	Yes	No
HT-151-01631	1.12" x 1.12"	PA66HIRH-SUV, Black, 100/pkg	0.18	0.18	Acrylic foam	-40°F to +176°F (-40°C to +80°C)	UL 94 HB (excluding adhesive)	-40°F to +221°F (-40°C to +105°C)	Yes	No
HT-151-01632	1.12" x 1.12"	PA66HIRH-SUV, Black, 500/pkg	0.18	0.18	Acrylic foam	-40°F to +176°F (-40°C to +80°C)	UL 94 HB (excluding adhesive)	-40°F to +221°F (-40°C to +105°C)	Yes	No
HT-151-03098	1.12" x 1.12"	PA666V0 T50, Black, 100/pkg	0.18	0.18	High heat high bond acrylate with base of acrylic foam	-	UL 94 V-0	-40°F to +248°F (-40°C to +120°C)	No	No

Part #	Dimensions	Material, Color, Qty.	Cable Tie Width Max	Mounting Hole Dia. (Imperial)	Adhesive	Adhesive Temp.	Flammability	Operating Temp.	UV Resistant	Reach Compliant (Art. 33)
HT-151-01633	1.49" x 1.49"	PA66HIRH-SUV, Black, 100/pkg	0.35	0.19	Acrylic foam	-40°F to +176°F (-40°C to +80°C)	UL 94 HB (excluding adhesive)	-40°F to +221°F (-40°C to +105°C)	Yes	No
HT-151-01634	1.49" x 1.49"	PA66HIRH-SUV, Black, 250/pkg	0.35	0.19	Acrylic foam	-40°F to +176°F (-40°C to +80°C)	UL 94 HB (excluding adhesive)	-40°F to +221°F (-40°C to +105°C)	Yes	No
HT-151-01857	1.5" x 1.5"	PA66HIRH-SUV, Black, 100/pkg	0.52	-	Acrylic foam	-40°F to +176°F (-40°C to +80°C)	UL 94 HB (excluding adhesive)	-40°F to +221°F (-40°C to +105°C)	Yes	No
HT-151-00646	1.12" x 1.12"	PA66UV, Black, 500/pkg	0.18	0.18	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	Yes	Yes
HT-151-00810	1.12" x 1.12"	PA66UV, Black, 100/pkg	0.18	0.18	Acrylate with base of acrylic foam	-31°F to +158°F (-35 °C to +70 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	Yes	No