

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Cable Ties for Automatic Systems

Part #	Description	Strength	Material, Color, Qty.	Flammability	UV Resistant	Reach Compliant (Art. 33)	Operating Temp.	Certs & Specs	Bundle Dia. (Imperial)	Reel Dia. (Imperial)	ROHS
HT-QTTIE0HS	Cable Tie for QS101	18lb Tensile Strength	PA66HSW, Black, 5000 Ties/Reel, 2 Reels/Carton	UL 94 V-2	Yes	No	40°F to +230°F (-40°C to +110°C)	UL ANSI/UL 1565 UL ANSI/UL 62275	0.7 - 16.0	18	Yes
HT-QTTIE9	Cable Tie for QS101	18lb Tensile Strength	PA66, Natural, 5000 Ties/Reel, 2 Reels/Carton	UL 94 V-2	No	No	-40°F to +185°F (-40°C to +85°C)	UL ANSI/UL 1565 UL ANSI/UL 62275	0.7 - 16.0	18	Yes
HT-120-05015	Cable Tie for AT2000	18lb Tensile Strength	PA46, Natural, 5000/reel	UL 94 V-2	No	No	-40°F to +275°F (-40°C to +135°C)	UL ANSI/UL 1565 UL ANSI/UL 62275	0.03 - 0.79	-	Yes
HT-T18RA5000	Cable Tie for AT2000	18lb Tensile Strength	PA66, Natural, 5000/reel	UL 94 V-2	No	No	-40°F to +185°F (-40°C to +85°C)	UL-ZODZ2. E64139 CAGE Code 53421	0.03 - 0.79	-	Yes
HT-T18RA5000HSW	Cable Tie for AT2000	18lb Tensile Strength	PA66HS, Black, 5000/reel	UL 94 V-2	No	No	-40°F to +257°F (-40°C to +125°C)	-	0.03 - 0.79	-	Yes
HT-T18RA50	Cable Tie for AT2000	18lb Tensile Strength	PA66, Natural, 50/bandolier, 500/pkg	UL 94 V-2	No	No	-40°F to +185°F (-40°C to +85°C)	CAGE Code 53421 UL-ZO-DZ2.E64139	0.03 - 0.79	-	Yes
HT-T18RA50HSW	Cable Tie for AT2000	18lb Tensile Strength	PA66HS, Black, 50/bandolier, 500/pkg	UL 94 V-2	No	No	-40°F to +257°F (-40°C to +125°C)	-	0.03 - 0.79	-	Yes
HT-T18RA50VO	Cable Tie for AT2000	18lb Tensile Strength	PA66V0, White, 50/bandolier, 500/pkg	UL 94 V-2	No	No	-40°F to +221°F (-40°C to +105°C)	UL ANSI/UL 62275 UL ANSI/UL 1565	0.03 - 0.79	-	Yes
HT-120-06001	MilSpec Cable Tie for AT2000, MS3367	18lb Tensile Strength	PA66, Natural, 50/bandolier, 500/pkg	UL 94 V-2	No	No	-40°F to +185°F (-40°C to +85°C)	SAE-AS33671 MS3367-4-9, Class 2	1.5 - 20.0 (Metric)	-	No

Part #	Description	Strength	Material, Color, Qty.	Flammability	UV Resistant	Reach Compliant (Art. 33)	Operating Temp.	Certs & Specs	Bundle Dia. (Imperial)	Reel Dia. (Imperial)	ROHS
HT-120-06002	MilSpec Cable Tie for AT2000, MS3367	18lb Tensile Strength	PA66, Natural, 5000/reel	UL 94 V-2	No	No	-40°F to +185°F (-40°C to +85°C)	SAE-AS33671 MS3367-4-9, Class 2	1.5 - 20.0 (Metric)	-	No
HT-T30RA30	Cable Ties for AT2060	30lb Tensile Strength	PA66, Natural, 30/bandolier, 600/pkg	UL 94 V-2	No	No	-40°F to +185°F (-40°C to +85°C)	CAGE Code 53421 UL-ZO-DZ2.E64139	0.06 - 1.25	17.7	No
HT-T30RA3000	Cable Ties for AT2060	30lb Tensile Strength	PA66, Natural, 3000/reel	UL 94 V-2	No	No	-40°F to +185°F (-40°C to +85°C)	CAGE Code 53421 UL-ZO-DZ2.E64139	0.06 - 1.25	17.7	Yes
HT-T30RA30000HS	Cable Ties for AT2060	30lb Tensile Strength	PA66HS, Black, 3000/reel	UL 94 V-2	No	No	-40°F to +257°F (-40°C to +125°C)	-	0.06 - 1.25	17.7	Yes
HT-T30RA300HS	Cable Ties for AT2060	30lb Tensile Strength	PA66HS, Black, 30/bandolier, 600/pkg	UL 94 V-2	No	No	-40°F to +257°F (-40°C to +125°C)	-	0.06 - 1.25	17.7	No
HT-ATS10266110	Cable Ties for ATS3080	50lb Tensile Strength	PA66HIRH-SUV, Black, 1640 ft/reel	UL 94 V-2	Yes	Yes	-40°F to +203°F (-40°C to +95°C)	-	0.31 - 3.14	15.25	Yes
HT-ATS10266210	Cable Ties for ATS3080	50lb Tensile Strength	PA66HSUV, Black, 5000/reel	UL 94 V-2	Yes	Yes	-40°F to +221°F (-40°C to +105°C)	-	0.31 - 3.14	15.25	Yes