

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Extended-Length Ties

Part #	Description	Material, Color, Qty.	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art. 33)
HT-TELS-SPOOL	Extended-Length Tie	POM, Black, 1-50 ft reel of strap/pkg	UL 94 HB	No	-40°F to +194°F (-40°C to +90°C)	Yes
HT-TELS-13	Extended-Length Tie	POM, Black, 10-13.5" straps and 10 heads/Kit	UL 94 HB	No	-40°F to +194°F (-40°C to +90°C)	No
HT-TELS-27	Extended-Length Tie	POM, Black, 10-27" straps and 10 heads/Kit	UL 94 HB	No	-40°F to +194°F (-40°C to +90°C)	No
HT-TELS-24STRAP	Extended-Length Tie	POM, Black, 25-24" straps/pkg	UL 94 HB	No	-40°F to +194°F (-40°C to +90°C)	No
HT-TELS-1	Extended-Length Tie	POM, Black, 50 ft reel of strap and 30 heads/Kit	UL 94 HB	No	-40°F to +194°F (-40°C to +90°C)	Yes
HT-TELS-H	Extended-Length Tie Heads	POM, Black, 25/pkg	UL 94 HB	No	-40°F to +194°F (-40°C to +90°C)	Yes
HT-TELS-SPK2	Extended-Length Tie Spacer	PP, Black, 50/pkg	UL 94 HB	No	-40°F to +239°F (-40°C to +115°C)	Yes