

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Flame Retardant Cable Ties

Part #	Descriptions	Length	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flamma-bility	Operating Temp.	UV Resistant	Reach Compliant (Art. 33)
HT-T18R9VOC2	Flame Retardant Cable Tie, UL Rated	4" Long	18lb Tensile Strength	PA66V0, Natural, 100/pkg	0.12 - 0.87	UL 94 V-0	-40°F to +212°F (-40°C to +100°C)	No	No
HT-T18R9VOM4	Flame Retardant Cable Tie, UL Rated	4" Long	18lb Tensile Strength	PA66V0, Natural, 1000/pkg	0.12 - 0.87	UL 94 V-0	-40°F to +212°F (-40°C to +100°C)	No	No
HT-T18I9VOM4	Flame Retardant Cable Tie, UL Rated	5.5" Long	18lb Tensile Strength	PA66V0, Natural, 1000/pkg	0.12 - 1.38	UL 94 V-0	-40°F to +212°F (-40°C to +100°C)	No	No
HT-T30R0VOC2	Flame Retardant Cable Tie, UL Rated	5.8" Long	30lb Tensile Strength	PA66V0, Black, 100/pkg	0.12 - 1.38	UL 94 V-0	-40°F to +212°F (-40°C to +100°C)	No	No
HT-T18L0VOC2	Flame Retardant Cable Tie, UL Rated	8" Long	18lb Tensile Strength	PA66V0, Black, 100/pkg	0.12 - 2.17	UL 94 V-0	-40°F to +212°F (-40°C to +100°C)	No	No
HT-T18L9VOM4	Flame Retardant Cable Tie, UL Rated	8" Long	18lb Tensile Strength	PA66V0, Natural, 1000/pkg	0.12 - 2.17	UL 94 V-0	-40°F to +212°F (-40°C to +100°C)	No	No
HT-T50R9VOM4	Flame Retardant Cable Tie, UL Rated	8" Long	50lb Tensile Strength	PA66V0, Natural, 1000/pkg	0.12 - 1.97	UL 94 V-0	-40°F to +212°F (-40°C to +100°C)	No	No