

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Flexiform Grommets

Part #	Panel Thickness	Material, Color, Qty.	Halogen Free	UV Resistant	Flammability	Operating Temp.	Reach Compliant (Art. 33)	US Mil Spec
HT-FPAA	0.016"-0.035"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-FTA	0.016"-0.051"	PTFE, Natural, 9.7ft/pkg	No	No	UL 94 V-0	-76°F to +500°F (-60°C to +260°C)	Yes	MS21266-1T
HT-FHA	0.016"-0.051"	PA6, Natural, 82ft/pkg	Yes	No	UL 94 HB	-76°F to +203°F (-60°C to +95°C)	Yes	MS21266-1N
HT-FPA	0.016"-0.051"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-FTB	0.051"-0.083"	PTFE, Natural, 9.7ft/pkg	No	No	UL 94 V-0	-76°F to +500°F (-60°C to +260°C)	Yes	MS21266-2T
HT-FHB	0.051"-0.083"	PA6, Natural, 82ft/pkg	Yes	No	UL 94 HB	-76°F to +203°F (-60°C to +95°C)	Yes	MS21266-2N
HT-FPB	0.051"-0.083"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-251-30309	0.083"-0.130"	PTFE, Natural, 9.7ft/pkg	No	No	MS21266-3T	-76°F to +500°F (-60°C to +260°C)	Yes	MS21266-3T
HT-FHC	0.083"-0.130"	PA6, Natural, 82ft/pkg	Yes	No	UL 94 HB	-76°F to +203°F (-60°C to +95°C)	Yes	MS21266-3N
HT-FPC	0.083"-0.130"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-FHD	0.130 "-0.189"	PA6, Natural, 82ft/pkg	Yes	No	UL 94 HB	-76°F to +203°F (-60°C to +95°C)	Yes	MS21266-4N
HT-FPD	0.130"-0.189"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-251-30509	0.189"-0.256"	PTFE, Natural, 9.7ft/pkg	No	No	UL 94 V-0	-76°F to +500°F (-60°C to +260°C)	Yes	MS21266-5T
HT-FPE	0.189"-0.256"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-FHE	0.189"-0.256"	PA6, Natural, 82ft/pkg	Yes	No	UL 94 HB	-76°F to +203°F (-60°C to +95°C)	Yes	MS21266-5N
HT-FHF	0.256"-0.319"	PA6, Natural, 82ft/pkg	Yes	No	UL 94 HB	-76°F to +203°F (-60°C to +95°C)	Yes	MS21266-6N

Part #	Panel Thickness	Material, Color, Qty.	Halogen Free	UV Resistant	Flammability	Operating Temp.	Reach Compliant (Art. 33)	US Mil Spec
HT-FPF	0.256"-0.319"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-251-30609	0.256"-0.319"	PTFE, Natural, 9.7ft/pkg	No	No	UL 94 V-0	-76°F to +500°F (-60°C to +260°C)	Yes	MS21266-6T
HT-FHG	0.319"-0.382"	PA6, Natural, 82ft/pkg	Yes	No	UL 94 HB	-76°F to +203°F (-60°C to +95°C)	Yes	MS21266-7N
HT-FPG	0.319"-0.382"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-FPH	0.382"-0.508"	PE, Natural, 82ft/pkg	Yes	No	UL 94 HB	-22°F to +176°F (-30°C to +80°C)	Yes	-
HT-251-30809	0.382"-0.508"	PTFE, Natural, 9.7ft/pkg	No	No	UL 94 V-0	-76°F to +500°F (-60°C to +260°C)	Yes	MS21266-8T
HT-SM1BK75MT	0.039"-0.079"	PVC, Black, 75m/roll	No	No	UL 94 HB	-85°F to +221°F (-65°C to +105°C)	Yes	-