

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Halogen Free Slotted Wiring Ducts

Halogen Free Slotted Wiring Duct, w/o Adhesive								
Part #	Dimensions	Material, Color	Qty.	Flammability	UV Resistant	Operating Temp.	Reach Compliant	Certs. & Specifications
HT-183-12525	25mm x 25mm	PC/ABS, Gray RAL	48 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	UL ANSI/UL 62275 EN [45545-2]
HT-183-12537	25mm x 37.5mm	PC/ABS, Gray RAL	54 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-12550	25mm x 50mm	PC/ABS, Gray RAL	44 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-22575	25mm x 75mm	PC/ABS, Gray RAL	36 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-13737	37.5mm x 37.5mm	PC/ABS, Gray RAL	40 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-13750	37.5mm x 50mm	PC/ABS, Gray RAL	32 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-13775	37.5mm x 75mm	PC/ABS, Gray RAL	24 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-05037	50mm x 37.5mm	PC/ABS, Gray RAL	32 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-15050	50mm x 50mm	PC/ABS, Gray RAL	42 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-15075	50mm x 75mm	PC/ABS, Gray RAL	28 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-17550	75mm x 50mm	PC/ABS, Gray RAL	28 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-17575	75mm x 75mm	PC/ABS, Gray RAL	24 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-11050	100mm x 50mm	PC/ABS, Gray RAL	20 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-11075	100mm x 75mm	PC/ABS, Gray RAL	16 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-12257	125mm x 75m	PC/ABS, Gray RAL	16 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	

Halogen Free Slotted Wiring Duct & Cover, w/o Adhesive

Part #	Dimensions	Material, Color	Qty.	Flammability	UV Resistant	Operating Temp.	Reach Compliant	Certs. & Specifications
HT-183-22525	25mm x 25mm	PC/ABS, Gray	50 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	UL ANSI/ UL 62275 UL ANSI/UL 1565 UL csa-C22.2 no. 62275 UL csa-C22.2 no. 18.5 EN [45545-2]
HT-183-22540	25mm x 40mm	PC/ABS, Gray	48 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-25060	25mm x 60mm	PC/ABS, Gray	60 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-22580	25mm x 80mm	PC/ABS, Gray	20 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-24025	40mm x 25mm	PC/ABS, Gray	48 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-24040	40mm x 40mm	PC/ABS, Gray	50 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-24060	40mm x 60mm	PC/ABS, Gray	40 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-24080	40mm x 80mm	PC/ABS, Gray	20 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-26040	60mm x 40mm	PC/ABS, Gray	40 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-26060	60mm x 60mm	PC/ABS, Gray	24 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-26080	60mm x 80mm	PC/ABS, Gray	20 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-26010	60mm x 100mm	PC/ABS, Gray	12 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-28060	80mm x 60mm	PC/ABS, Gray	20 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-28080	80mm x 80mm	PC/ABS, Gray	12 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-28010	80mm x 100mm	PC/ABS, Gray	10 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-21010	100mm x 100mm	PC/ABS, Gray	8 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-22040	100mm x 40mm	PC/ABS, Gray	20 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	

Halogen Free Slotted Wiring Duct & Cover, w/o Adhesive

Part #	Dimensions	Material, Color	Qty.	Flammability	UV Resistant	Operating Temp.	Reach Compliant	Certs. & Specifications
HT-183-21060	100mm x 60mm	PC/ABS, Gray	16 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	UL ANSI/ UL 62275 UL ANSI/UL 1565 UL csa-C22.2 no. 62275 UL csa-C22.2 no. 18.5 EN [45545-2]
HT-183-21080	100mm x 80mm	PC/ABS, Gray	12 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-21260	120mm x 60mm	PC/ABS, Gray	12 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	
HT-183-21280	120mm x 80mm	PC/ABS, Gray	16 m/Box	UL 94 V-0	No	-13°F to +194°F (-25°C to +90°C)	Yes	