

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® HelaDuct Wiring Duct

Part #	Description	Dimensions	Material, Color, Qty.	Flammability	Halogen Free	UV Resistant	Operating Temp	Adhesive	Adhesive Temp.	Reach Compliant
HT-164-11008	HelaDuct Flex10 Wiring Duct, Non-Adhesive	0.39" Dia., 19.7" Length	PP, White, 100/ctn	UL 94 V-0 (excluding adhesive)	Yes	No	-4°F to +158°F (-20°C to +70°C)	-	-	Yes
HT-164-11108	HelaDuct Flex10SK Wiring Duct, Adhesive	0.39" Dia., 19.7" Length	PP, White, 100/ctn	UL 94 V-0 (excluding adhesive)	Yes	No	-4°F to +158°F (-20°C to +70°C)	Synthetic rubber with base of polyethylene foam	-40°F to +176°F (-40°C to +80°C)	Yes
HT-164-21008	HelaDuct Flex20 Wiring Duct, Non-Adhesive	0.78" Dia., 19.7" Length	PP, White, 70/ctn	UL 94 V-0 (excluding adhesive)	Yes	No	-4°F to +158°F (-20°C to +70°C)	-	-	Yes
HT-164-21108	HelaDuct Flex20SK Wiring Duct, Adhesive	0.78" Dia., 19.7" Length	PP, White, 70/ctn	UL 94 V-0 (excluding adhesive)	Yes	No	-4°F to +158°F (-20°C to +70°C)	Synthetic rubber with base of polyethylene foam	-40°F to +176°F (-40°C to +80°C)	Yes
HT-164-31008	HelaDuct Flex30 Wiring Duct, Non-Adhesive	1.18" Dia., 19.7" Length	PP, White, 40/ctn	UL 94 V-0 (excluding adhesive)	Yes	No	-4°F to +158°F (-20°C to +70°C)	-	-	Yes
HT-164-31108	HelaDuct Flex30SK Wiring Duct, Adhesive	1.18" Dia., 19.7" Length	PP, White, 40/ctn	UL 94 V-0 (excluding adhesive)	Yes	No	-4°F to +158°F (-20°C to +70°C)	Synthetic rubber with base of polyethylene foam	-40°F to +176°F (-40°C to +80°C)	Yes
HT-164-41008	HelaDuct Flex40 Wiring Duct, Non-Adhesive	1.57" Dia., 19.7" Length	PP, White, 24/ctn	UL 94 V-0 (excluding adhesive)	Yes	No	-4°F to +158°F (-20°C to +70°C)	-	-	Yes
HT-164-41108	HelaDuct Flex40SK Wiring Duct, Adhesive	1.57" Dia., 19.7" Length	PP, White, 24/ctn	UL 94 V-0 (excluding adhesive)	Yes	No	-4°F to +158°F (-20°C to +70°C)	Synthetic rubber with base of polyethylene foam	-40°F to +176°F (-40°C to +80°C)	Yes