

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® HelaGuard Flexible Metallic Conduit

Part #	Description	Diameter	Material, Quantity	Length (Imperial)	UV Resistant	Operating Temp	Reach Compliant (Article 33)	ROHS
HT-SSU10-10M	HelaGuard Metallic Conduit, Extra Flexible	0.25" (10mm) Dia	SS316, Metal, 32.8 ft/reel	32.8	No	-148°F to +752°F (-100°C to +400°C)	No	No
HT-SSU16-10M	HelaGuard Metallic Conduit, Extra Flexible	0.38" (16mm) Dia	SS316, Metal, 32.8 ft/reel	32.8	No	-148°F to +752°F (-100°C to +400°C)	No	No
HT-SSU20-25M	HelaGuard Metallic Conduit, Extra Flexible	0.50" (20mm) Dia	SS316, Metal, 82 ft/reel	82.0	No	-148°F to +752°F (-100°C to +400°C)	No	No
HT-SSU32-25M	HelaGuard Metallic Conduit, Extra Flexible	1" (32mm) Dia	SS316, Metal, 82.0 ft/reel	82.0	No	-148°F to +752°F (-100°C to +400°C)	No	No
HT-LTPH-C20B-25M	HelaGuard Spiral Metallic Conduit, Flexible	0.50" (20mm) Dia	GS/TPE, Black, 82ft/Reel	82.0	No	-76°F to +302°F (-60°C to +150°C)	Yes	Yes