

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Helawrap & Accessories

Part#	Description	Diameter	Material, Color, Qt.	Bundle Diameter (Imperial)	Flammability	Operating Temp.	Halogen Free	UV Resistant	Reach Compliant (Article 33)	Certification/ Specifications
HT-161-62000	Helawrap, HWPP16, Convenience Pack	5/8" (16mm) Dia	PP, Black, 10ft/pkg	0.51 - 0.63	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	-
HT-161-64217	Helawrap, HWPP16, Convenience Pack	5/8" (16mm) Dia	PP, White, 10ft/pkg	0.51 - 0.63	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG-LAB ECE R-118-03 Abschnitt 6 / Annex 6
HT-161-62001	Helawrap, HWPP25, Convenience Pack	1" (25mm) Dia	PP, Black, 10ft/pkg	0.91 - 1.06	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	-
HT-161-64417	Helawrap, HWPP25, Convenience Pack	1" (25mm) Dia	PP, White, 10ft/pkg	0.91 - 1.06	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG-LAB ECE R-118-03 Abschnitt 6 / Annex 6
HT-161-63103	Helawrap, HWPAV08	5/16" (8mm) Dia	PA6V0, Black, 100 ft/reel	0.28 - 0.36	UL 94 V-0	-40°F to +194°F (-40°C to +90°C)	Yes	No	Yes	EN [45545-2] UL UL 1441
HT-161-64112	Helawrap, HWPP08	5/16" (8mm) Dia	PP, Black, 100 ft/reel	0.31 - 0.36	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG ECE R 118-03 Abschnitt 6
HT-161-63203	Helawrap, HWPAV016	5/8" (16mm) Dia	PA6V0, Black, 100 ft/reel	0.51 - 0.63	UL 94 V-0	-40°F to +194°F (-40°C to +90°C)	Yes	No	Yes	EN [45545-2] UL UL 1441
HT-161-64213	Helawrap, HWPP16	5/8" (16mm) Dia	PP, Black, 100 ft/reel	0.51 - 0.63	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG ECE R 118-03 Abschnitt 6
HT-161-64216	Helawrap, HWPP16	5/8" (16mm) Dia	PP, White, 100 ft/reel	0.51 - 0.63	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG-LAB ECE R-118-03 Abschnitt 6 / Annex 6
HT-161-63303	Helawrap, HWPAV020	3/4" (20mm) Dia	PA6V0, Black, 100 ft/reel	0.71 - 0.83	UL 94 V-0	-40°F to +194°F (-40°C to +90°C)	Yes	No	Yes	EN [45545-2] UL UL 1441
HT-161-64310	Helawrap, HWPP20	3/4" (20mm) Dia	PP, Black, 100 ft/reel	0.71 - 0.83	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG ECE R 118-03 Abschnitt 6
HT-161-64311	Helawrap, HWPP20	3/4" (20mm) Dia	PP, White, 100 ft/reel	0.71 - 0.83	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG-LAB ECE R-118-03 Abschnitt 6 / Annex 6

Part#	Description	Diameter	Material, Color, Qt.	Bundle Diameter (Imperial)	Flammability	Operating Temp.	Halogen Free	UV Resistant	Reach Compliant (Article 33)	Certification/ Specifications
HT-161-63403	Helawrap, HWPAV025	1" (25mm) Dia	PA6V0, Black, 100 ft/reel	0.91 - 1.06	UL 94 V-0	-40°F to +194°F (-40°C to +90°C)	Yes	No	Yes	UL UL 1441 EN [45545-2]
HT-161-64414	Helawrap, HWPP25	1" (25mm) Dia	PP, Black, 100 ft/reel	0.91 - 1.06	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG ECE R 118-03 Abschnitt 6
HT-161-64416	Helawrap, HWPP25	1" (25mm) Dia	PP, White, 100 ft/ reel	0.91 - 1.06	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG-LAB ECE R-118-03 Abschnitt 6 / Annex 6
HT-161-63501	Helawrap, HWPAV030	1-1/4" (30mm) Dia	PA6V0, Black, 82ft/ Reel	1.14 - 1.26	UL 94 V-0	-40°F to +194°F (-40°C to +90°C)	Yes	No	Yes	UL UL 1441 EN [45545-2]
HT-161-63503	Helawrap, HWPAV030	1-1/4" (30mm) Dia	PA6V0, Black, 100 ft/reel	1.14 - 1.26	UL 94 V-0	-40°F to +194°F (-40°C to +90°C)	Yes	No	Yes	UL UL 1441 EN [45545-2]
HT-161-64507	Helawrap, HWPP30	1-1/4" (30mm) Dia	PP, Black, 100 ft/reel	1.14 - 1.26	UL 94 HB	-76°F to +230°F (-60°C to +110°C)	Yes	No	Yes	EDAG ECE R 118-03 Abschnitt 6
HT-161-60001	Helawrap, Application Tool for HWPP08 and HWP6V08	5/16"	PA66, Blue, 10/pkg	-	-	-	Yes	No	Yes	-
HT-161-60002	Helawrap, Application Tool for HWPP16 and HWP6V016	5/8"	PA66, Blue, 10/pkg	-	-	-	Yes	No	Yes	-
HT-161-60003	Helawrap, Application Tool for HWPP20 and HWP6V020	3/4"	PA66, Blue, 10/pkg	-	-	-	Yes	No	Yes	-
HT-161-60004	Helawrap, Application Tool for HWPP25 and HWP6V025	1"	PA66, Blue, 10/pkg	-	-	-	Yes	No	Yes	-
HT-161-60005	Helawrap, Application Tool for HWPP30 and HWP6V030	1-1/4"	PA66, Blue, 10/pkg	-	-	-	Yes	No	Yes	-
HT-161-64002	Helawrap, Accessory Clip, HWCLIP08	5/16" Dia	PA66HIRHS, Black, 50/pkg	-	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	No	Yes	-
HT-161-64004	Helawrap, Accessory Clip, HWCLIP16	5/8" Dia	PA66HIRHS, Black, 50/pkg	-	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	No	Yes	-
HT-161-64006	Helawrap, Accessory Clip, HWCLIP20	3/4" Dia	PA66HIRHS, Black, 50/pkg	-	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	No	Yes	-
HT-161-64008	Helawrap, Accessory Clip, HWCLIP25	1" Dia	PA66HIRHS, Black, 50/pkg	-	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	No	Yes	-
HT-161-64010	Helawrap, Accessory Clip, HWCLIP30	1-1/4" Dia	PA66HIRHS, Black, 50/pkg	-	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	No	Yes	-

Part#	Description	Diameter	Material, Color, Qt.	Bundle Diameter (Imperial)	Flammability	Operating Temp.	Halogen Free	UV Resistant	Reach Compliant (Article 33)	Certification/ Specifications
HT-161-64013	Helawrap, Mounting Base with Adhesive, HWBASEA	-	PA66HIRHS, Black, 50/pkg	-	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	No	Yes	-
HT-161-64014	Helawrap, Mounting Base without Adhesive, HWBASE	-	PA66HIRHS, Black, 50/pkg	-	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	No	Yes	-
HT-201-20010	Protective Strap for Helawrap HWCLIP25 and HWCLIP30	-	PVC, Black, 500/pkg	-	UL 94 V-2	-31°F to +122°F (-35°C to +50°C)	No	No	Yes	-