

# PRODUCT SPECIFICATION SHEET

**Product Name: HellermannTyton® Kabelrap Ties and Tools**

| Part #       | Description | Tension Setting Tools | Cable Ties         | Material, Color, Qty. | UV Resistant | Reach Compliant |
|--------------|-------------|-----------------------|--------------------|-----------------------|--------------|-----------------|
| HT-121-00680 | KR6/8 Tool  | Manual                | KR6 and KR8 series | Metal, Blue;Red, 1/EA | No           | No              |

| Part #       | Description                 | Length     | Strength               | Material, Color, Qty.   | Tie Closure    | Bundle Dia. (Imperial) | UV Resistant | Flammability | Operating Temp.                   | Reach Compliant | Certs & Specs.                       |
|--------------|-----------------------------|------------|------------------------|-------------------------|----------------|------------------------|--------------|--------------|-----------------------------------|-----------------|--------------------------------------|
| HT-121-82119 | Kabelrap Tie                | 8.3" Long  | 176lb Tensile Strength | PA66, Natural, 50/pkg   | Fiberglass Pin | 0.32 - 1.9             | No           | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C)  | Yes             | DNV GL   IEC 62275:2006 EN [45545-2] |
| HT-121-82160 | Kabelrap Tie                | 8.3" Long  | 176lb Tensile Strength | PA66UV, Black, 50/pkg   | Fiberglass Pin | 0.32 - 1.9             | Yes          | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C)  | Yes             | DNV GL   IEC 62275:2006              |
| HT-121-73390 | Cable Tie without Serration | 13.3" Long | 176lb Tensile Strength | PA66HS, Black, 50/pkg   | Fiberglass Pin | 8.0-86.0 (Metric)      | No           | UL 94 V-2    | -40°F to +221°F (-40°C to +105°C) | Yes             | -                                    |
| HT-121-83355 | Kabelrap Tie                | 13.3" Long | 176lb Tensile Strength | PA66HS, Natural, 50/pkg | Fiberglass Pin | 0.32 - 3.4             | No           | UL 94 V-2    | -40°F to +221°F (-40°C to +105°C) | Yes             | -                                    |
| HT-121-83360 | Kabelrap Tie                | 13.3" Long | 176lb Tensile Strength | PA66UV, Black, 50/pkg   | Fiberglass Pin | 0.32 - 3.4             | Yes          | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C)  | Yes             | DNV GL   IEC 62275:2006              |
| HT-121-83378 | Kabelrap Tie                | 13.3" Long | 176lb Tensile Strength | PA46, Gray, 50/pkg      | Fiberglass Pin | 0.32 - 3.4             | No           | UL 94 V-2    | -40°F to +302°F (-40°C to +150°C) | Yes             | -                                    |
| HT-121-63560 | Kabelrap Tie                | 14" Long   | 110lb Tensile Strength | PA66UV, Black, 50/pkg   | Fiberglass Pin | 0.19 - 3.7             | Yes          | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C)  | Yes             | DNV GL   IEC 62275:2006              |
| HT-121-74359 | Kabelrap Tie                | 16.8" Long | 176lb Tensile Strength | PA66HS, Natural, 50/pkg | Fiberglass Pin | 0.32 - 4.1             | No           | UL 94 V-2    | -40°F to +221°F (-40°C to +105°C) | Yes             | -                                    |