

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® MOC Clip to MOC Clip Perpendicular

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-01924	MOC Clip to MOC Clip Perpendicular	5 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.07 X 0.43	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01925	MOC Clip to MOC Clip Perpendicular	5 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.06 X 0.44	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01926	MOC Clip to MOC Clip Perpendicular	5 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.10 X 0.46	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01927	MOC Clip to MOC Clip Perpendicular	5 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.18 X 0.52	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01928	MOC Clip to MOC Clip Perpendicular	5 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.26 X 0.59	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01929	MOC Clip to MOC Clip Perpendicular	5 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.35 X 0.67	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01930	MOC Clip to MOC Clip Perpendicular	5 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.45 X 0.74	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01931	MOC Clip to MOC Clip Perpendicular	5 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.52 X 0.82	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01932	MOC Clip to MOC Clip Perpendicular	5 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.60 X 0.90	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01933	MOC Clip to MOC Clip Perpendicular	5 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	1.87 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01934	MOC Clip to MOC Clip Perpendicular	5 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.16-0.22	2.02 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-01935	MOC Clip to MOC Clip Perpendicular	5 mm, 26 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.16-0.22	2.19 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01948	MOC Clip to MOC Clip Perpendicular	6 mm, 5 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.06 X 0.47	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01949	MOC Clip to MOC Clip Perpendicular	6 mm, 6 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.11 X 0.47	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01950	MOC Clip to MOC Clip Perpendicular	6 mm, 7 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.15 X 0.47	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01951	MOC Clip to MOC Clip Perpendicular	6 mm, 8 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.23 X 0.52	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01952	MOC Clip to MOC Clip Perpendicular	6 mm, 9 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.31 X 0.59	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01953	MOC Clip to MOC Clip Perpendicular	6 mm, 10 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.40 X 0.67	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01954	MOC Clip to MOC Clip Perpendicular	6 mm, 12 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.50 X 0.74	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01955	MOC Clip to MOC Clip Perpendicular	6 mm, 14 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.57 X 0.82	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01956	MOC Clip to MOC Clip Perpendicular	6 mm, 16 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.65 X 0.90	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01957	MOC Clip to MOC Clip Perpendicular	6 mm, 19 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	1.92 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01958	MOC Clip to MOC Clip Perpendicular	6 mm, 22 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	2.07 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01959	MOC Clip to MOC Clip Perpendicular	6 mm, 26 mm Perpendicular	PA66HIRH- SUV, Black, 2000/ctn	0.22-0.27	2.24 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-01972	MOC Clip to MOC Clip Perpendicular	7 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.10 X 0.53	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01973	MOC Clip to MOC Clip Perpendicular	7 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.15 X 0.53	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01974	MOC Clip to MOC Clip Perpendicular	7 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.19 X 0.53	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01975	MOC Clip to MOC Clip Perpendicular	7 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	1.27 X 0.53	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01976	MOC Clip to MOC Clip Perpendicular	7 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.35 X 0.59	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01977	MOC Clip to MOC Clip Perpendicular	7 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.44 X 0.67	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01978	MOC Clip to MOC Clip Perpendicular	7 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.54 X 0.74	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01979	MOC Clip to MOC Clip Perpendicular	7 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.61 X 0.82	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01980	MOC Clip to MOC Clip Perpendicular	7 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.69 X 0.90	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01981	MOC Clip to MOC Clip Perpendicular	7 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.96 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01982	MOC Clip to MOC Clip Perpendicular	7 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	2.11 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01983	MOC Clip to MOC Clip Perpendicular	7 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	2.28 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01996	MOC Clip to MOC Clip Perpendicular	8 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	1.15 X 0.60	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-01997	MOC Clip to MOC Clip Perpendicular	8 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	1.19 X 0.60	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01998	MOC Clip to MOC Clip Perpendicular	8 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.24-0.31	1.24 X 0.60	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-01999	MOC Clip to MOC Clip Perpendicular	8 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	1.32 X 0.60	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02011	MOC Clip to MOC Clip Perpendicular	8 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	1.4 X 0.60	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02012	MOC Clip to MOC Clip Perpendicular	8 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	1.49 X 0.67	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02013	MOC Clip to MOC Clip Perpendicular	8 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 1000/ctn	0.28-0.35	1.59 X 0.74	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02014	MOC Clip to MOC Clip Perpendicular	8 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	1.66 X 0.82	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02015	MOC Clip to MOC Clip Perpendicular	8 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	1.74 X 0.90	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02016	MOC Clip to MOC Clip Perpendicular	8 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	2.01 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02017	MOC Clip to MOC Clip Perpendicular	8 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	2.16 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02018	MOC Clip to MOC Clip Perpendicular	8 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.28-0.35	2.34 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02031	MOC Clip to MOC Clip Perpendicular	9 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.19 X 0.68	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02032	MOC Clip to MOC Clip Perpendicular	9 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.24 X 0.68	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-02033	MOC Clip to MOC Clip Perpendicular	9 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.28 X 0.68	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02034	MOC Clip to MOC Clip Perpendicular	9 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.36 X 0.68	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02035	MOC Clip to MOC Clip Perpendicular	9 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.44 X 0.68	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02036	MOC Clip to MOC Clip Perpendicular	9 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.54 X 0.68	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02037	MOC Clip to MOC Clip Perpendicular	9 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.63 X 0.74	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02038	MOC Clip to MOC Clip Perpendicular	9 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.70 X 0.82	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02039	MOC Clip to MOC Clip Perpendicular	9 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	1.78 X 0.90	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02040	MOC Clip to MOC Clip Perpendicular	9 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	2.05 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02041	MOC Clip to MOC Clip Perpendicular	9 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	2.20 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02042	MOC Clip to MOC Clip Perpendicular	9 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.31-0.39	2.38 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02055	MOC Clip to MOC Clip Perpendicular	10 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.26 X 0.77	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02056	MOC Clip to MOC Clip Perpendicular	10 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.31 X 0.77	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02057	MOC Clip to MOC Clip Perpendicular	10 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.35 X 0.77	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-02058	MOC Clip to MOC Clip Perpendicular	10 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.43 X 0.77	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02059	MOC Clip to MOC Clip Perpendicular	10 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.51 X 0.77	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02060	MOC Clip to MOC Clip Perpendicular	10 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.60 X 0.77	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02061	MOC Clip to MOC Clip Perpendicular	10 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.70 X 0.77	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02062	MOC Clip to MOC Clip Perpendicular	10 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.77 X 0.82	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02063	MOC Clip to MOC Clip Perpendicular	10 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	1.85 X 0.90	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02064	MOC Clip to MOC Clip Perpendicular	10 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	2.12 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02065	MOC Clip to MOC Clip Perpendicular	10 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	2.27 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02066	MOC Clip to MOC Clip Perpendicular	10 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.37-0.45	2.45 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02079	MOC Clip to MOC Clip Perpendicular	12 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	1.33 X 0.87	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02080	MOC Clip to MOC Clip Perpendicular	12 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	1.38 X 0.87	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02081	MOC Clip to MOC Clip Perpendicular	12 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 1000/ctn	0.41-0.54	1.42 X 0.87	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02082	MOC Clip to MOC Clip Perpendicular	12 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	1.50 X 0.87	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-02083	MOC Clip to MOC Clip Perpendicular	12 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	1.58 X 0.87	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02084	MOC Clip to MOC Clip Perpendicular	12 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	1.68 X 0.87	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02085	MOC Clip to MOC Clip Perpendicular	12 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	1.77 X 0.87	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02086	MOC Clip to MOC Clip Perpendicular	12 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	1.84 X 0.87	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02087	MOC Clip to MOC Clip Perpendicular	12 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	1.92 X 0.90	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02088	MOC Clip to MOC Clip Perpendicular	12 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	2.19 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02089	MOC Clip to MOC Clip Perpendicular	12 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	2.34 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02090	MOC Clip to MOC Clip Perpendicular	12 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.41-0.54	2.52 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02103	MOC Clip to MOC Clip Perpendicular	14 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	1.42 X 0.94	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02104	MOC Clip to MOC Clip Perpendicular	14 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	1.46 X 0.94	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02105	MOC Clip to MOC Clip Perpendicular	14 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	1.51 X 0.94	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02106	MOC Clip to MOC Clip Perpendicular	14 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	1.59 X 0.94	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02107	MOC Clip to MOC Clip Perpendicular	14 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	1.67 X 0.94	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-02108	MOC Clip to MOC Clip Perpendicular	14 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	1.76 X 0.94	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02109	MOC Clip to MOC Clip Perpendicular	14 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	1.86 X 0.94	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02110	MOC Clip to MOC Clip Perpendicular	14 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	1.93 X 0.94	0.39	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02111	MOC Clip to MOC Clip Perpendicular	14 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	2.00 X 0.94	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02112	MOC Clip to MOC Clip Perpendicular	14 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	2.28 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02113	MOC Clip to MOC Clip Perpendicular	14 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	2.43 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02114	MOC Clip to MOC Clip Perpendicular	14 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.51-0.62	2.60 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02127	MOC Clip to MOC Clip Perpendicular	16 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	1.48 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02128	MOC Clip to MOC Clip Perpendicular	16 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	1.53 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02129	MOC Clip to MOC Clip Perpendicular	16 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	1.57 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02130	MOC Clip to MOC Clip Perpendicular	16 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	1.66 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02131	MOC Clip to MOC Clip Perpendicular	16 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	1.74 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02132	MOC Clip to MOC Clip Perpendicular	16 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	1.83 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-02133	MOC Clip to MOC Clip Perpendicular	16 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	1.93 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02134	MOC Clip to MOC Clip Perpendicular	16 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	2.00 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02135	MOC Clip to MOC Clip Perpendicular	16 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	2.07 X 1.01	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02136	MOC Clip to MOC Clip Perpendicular	16 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	2.35 X 1.07	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02137	MOC Clip to MOC Clip Perpendicular	16 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	2.49 X 1.20	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02138	MOC Clip to MOC Clip Perpendicular	16 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.55-0.72	2.67 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02151	MOC Clip to MOC Clip Perpendicular	19 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	1.68 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02152	MOC Clip to MOC Clip Perpendicular	19 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	1.73 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02153	MOC Clip to MOC Clip Perpendicular	19 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	1.77 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02154	MOC Clip to MOC Clip Perpendicular	19 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	1.85 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02155	MOC Clip to MOC Clip Perpendicular	19 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	1.93 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02156	MOC Clip to MOC Clip Perpendicular	19 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	2.02 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02157	MOC Clip to MOC Clip Perpendicular	19 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	2.12 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-02158	MOC Clip to MOC Clip Perpendicular	19 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	2.19 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02159	MOC Clip to MOC Clip Perpendicular	19 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	2.26 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02160	MOC Clip to MOC Clip Perpendicular	19 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	2.54 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02161	MOC Clip to MOC Clip Perpendicular	19 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	2.69 X 1.29	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02162	MOC Clip to MOC Clip Perpendicular	19 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.67-0.86	2.86 X 1.36	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02175	MOC Clip to MOC Clip Perpendicular	22 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	1.80 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02176	MOC Clip to MOC Clip Perpendicular	22 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	1.85 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02177	MOC Clip to MOC Clip Perpendicular	22 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	1.89 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02178	MOC Clip to MOC Clip Perpendicular	22 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	1.97 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02179	MOC Clip to MOC Clip Perpendicular	22 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	2.05 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02180	MOC Clip to MOC Clip Perpendicular	22 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	2.15 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02181	MOC Clip to MOC Clip Perpendicular	22 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	2.24 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02182	MOC Clip to MOC Clip Perpendicular	22 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	2.31 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-02183	MOC Clip to MOC Clip Perpendicular	22 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	2.39 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02184	MOC Clip to MOC Clip Perpendicular	22 mm, 19 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.79-0.98	2.67 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02185	MOC Clip to MOC Clip Perpendicular	22 mm, 22 mm Perpendicular	PA66HIRH-SUV, Black, 1000/ctn	0.79-0.98	2.81 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02186	MOC Clip to MOC Clip Perpendicular	22 mm, 26 mm Perpendicular	PA66HIRH-SUV, Black, 1000/ctn	0.79-0.98	2.99 X 1.44	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02199	MOC Clip to MOC Clip Perpendicular	26 mm, 5 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.91-1.14	1.96 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02200	MOC Clip to MOC Clip Perpendicular	26 mm, 6 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.91-1.14	2.01 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02201	MOC Clip to MOC Clip Perpendicular	26 mm, 7 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.91-1.14	2.05 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02202	MOC Clip to MOC Clip Perpendicular	26 mm, 8 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.91-1.14	2.13 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02203	MOC Clip to MOC Clip Perpendicular	26 mm, 9 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.91-1.14	2.21 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02204	MOC Clip to MOC Clip Perpendicular	26 mm, 10 mm Perpendicular	PA66HIRH-SUV, Black, 1000/ctn	0.91-1.14	2.30 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02205	MOC Clip to MOC Clip Perpendicular	26 mm, 12 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.91-1.14	2.40 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02206	MOC Clip to MOC Clip Perpendicular	26 mm, 14 mm Perpendicular	PA66HIRH-SUV, Black, 2000/ctn	0.91-1.14	2.47 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02207	MOC Clip to MOC Clip Perpendicular	26 mm, 16 mm Perpendicular	PA66HIRH-SUV, Black, 1000/ctn	0.91-1.14	2.55 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No

Part #	Descrip.	Dimensions	Material, Color, Qty.	Bundle Dia (Imperial)	L X H (Imperial)	Depth (Imperial)	Halogen Free	Flammability	Operating Temp.	UV Resist.	Reach Compliant
HT-156-02208	MOC Clip to MOC Clip Perpendicular	26 mm, 19 mm Perpen- dicular	PA66HIRH- SUV, Black, 2000/ctn	0.91-1.14	2.82 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02209	MOC Clip to MOC Clip Perpendicular	26 mm, 22 mm Perpen- dicular	PA66HIRH- SUV, Black, 2000/ctn	0.91-1.14	2.97 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No
HT-156-02210	MOC Clip to MOC Clip Perpendicular	26 mm, 26 mm Perpen- dicular	PA66HIRH- SUV, Black, 1000/ctn	0.91-1.14	3.14 X 1.61	0.47	Yes	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	No