

# PRODUCT SPECIFICATION SHEET

## Product Name: HellermannTyton® Offset Fir Tree Mounts

Part #	Strength (Imperial)	Offset	Dimensions (L x W)	Fixation Method	Mounting Hole Dia. (Metric)	Disc Dia. (Imperial)	Flammability	Operating Temp.	Material, Color	UV Resist	Reach Compliant (Art. 33)
HT-157-00424	50	12.5mm Offset	8.5"L x 0.19"W	Fir Tree	6.1 - 6.9 mm 6.35 mm (hexagonal)	0.59	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	No
HT-157-00425	50	12.5mm Offset	8.5"L x 0.19"W	Fir tree for round holes	6.1 - 7.0 mm 6.1 - 6.6 mm (hexagonal)	0.59	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, BK	Yes	No
HT-157-00428	50	12.5mm Offset	8.5"L x .19"W	-	6.2 x 12.2 mm 6.5 x 13.0 mm 7.0 x 12.0 mm 6.5 x 12.5 mm	0.69 " x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	No
HT-157-00366	50	12.5mm Offset	8.5"L x 0.19"W	Fir tree	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.59	-	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	No
HT-157-00367	50	12.5mm Offset	8.5"L x 0.19"W	Fir tree	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.59	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	No
HT-157-00171	50	12.5mm Offset	8.5"L x .19"W	Fir tree for round holes	6.1 - 7.0 mm 6.1 - 6.6 mm (hexagonal)	0.59	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00312	50	12.5mm Offset	8.5"L x .19"W	fir tree for round holes	6.1 - 7.0 mm 6.1 - 6.6 mm (hexagonal)	0.59	-	-40°F to +266°F (-40°C to +130°C)	PA46, Brown	No	No
HT-157-00246	50	12.5mm Offset	8.5"L x 0.19"W	Fir Tree	6.1 - 6.9 mm 6.1 - 6.6 mm (hexagonal)	0.60	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00145	50	12.5 mm Offset	8.5"L x 0.19"W	Fir Tree	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.59	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00130	50	12.5 mm Offset	8.5"L x 0.19"W	Fir Tree	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.59	UL 94 V-2	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	Yes
HT-157-00165	50	12.5 mm Offset/90° Angle	8.7"L x .20"W	Fir tree for round holes	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.59	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes

Part #	Strength (Imperial)	Offset	Dimensions (L x W)	Fixation Method	Mounting Hole Dia. (Metric)	Disc Dia. (Imperial)	Flammability	Operating Temp.	Material, Color	UV Resist	Reach Compliant (Art. 33)
HT-157-00118	1-Pc Cable Tie/Offset Fir Tree w/ Disc50	12.5 mm Offset	8.5"L x .19"W	Fir tree for round holes	M6	0.59	-	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	Yes
HT-157-00131	50	12.5 mm Offset	8.5"L x .19"W	Fir tree for round holes	M6	0.59	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00249	50	12.5 mm Offset	8.5"L x .18"W	Fir tree for oval holes	6.2 x 12.2 mm 6.5 x 12.5 mm 7.0 x 12.0 mm 6.5 x 13.0 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	No	Yes
HT-157-00224	50	12.5 mm Offset	8.5"L x .18"W	Fir tree for oval holes	6.5 x 12.5 mm 6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 13.0 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00225	50	12.5 mm Offset	8.5"L x .18"W	Fir tree for oval holes	6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm	0.69 x 0.93	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	Yes	No
HT-157-00216	50	12.5 mm Offset	9.2"L x .20"W	Fir tree for round holes	6.1 - 6.9 mm	0.65	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00200	50	25mm Offset	9.1"L x 0.19"W	Fir tree	6.1 - 6.9 mm 6.35 mm (hexagonal)	0.75	-	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Natural	No	Yes
HT-157-00169	50	25mm Offset	9.1"L x 0.19"W	Fir tree	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.75	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00167	50	25mm Offset	9.1"L x .20"W	Fir tree	4.8 - 5.2 mm	0.75	-	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	No
HT-157-00170	50	25mm Offset	9.1"L x .75"W	Fir tree	7.6 - 8.4 mm	0.75	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00214	50	25mm Offset	9.7"L x .20"W	Fir tree	6.1 - 6.9 mm	0.75	-	-40°F to +266°F (-40°C to +130°C)	PA46, Black	No	No
HT-157-00432	50	25mm Offset	9"L x .19"W	-	6.5 x 13.0 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm	0.69 " x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, BK	Yes	No
HT-157-00431	50	25mm Offset	9.0"L x .19"W	-	7.0 x 12.0 mm 6.5 x 12.5 mm 6.5 x 13.0 mm 6.2 x 12.2 mm	0.69 " x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	No
HT-157-00186	50	25mm Offset	9.1"L x .19"W	Fir tree	6.1 - 7.0 mm 6.1 - 6.6 mm (hexagonal)	0.75	-	-40°F to +266°F (-40°C to +130°C)	PA46, Brown	No	Yes

Part #	Strength (Imperial)	Offset	Dimensions (L x W)	Fixation Method	Mounting Hole Dia. (Metric)	Disc Dia. (Imperial)	Flammability	Operating Temp.	Material, Color	UV Resist	Reach Compliant (Art. 33)
HT-157-00368	50	25mm Offset	9.1"L x .20"W	Fir tree	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.75	-	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	No
HT-157-00158	50	25 mm Offset	9.1"L x .19"W	Fir tree	6.1 - 6.9 mm 6.35 mm (hexagonal)	0.75	-	-40°F to +266°F (-40°C to +130°C)	PA46, Brown	No	Yes
HT-157-00150	50	25 mm Offset	9.1"L x .20"W	Fir tree for round holes	6.1 - 6.9 mm 6.35 mm (hexagonal)	0.75	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00119	50	25 mm Offset	9.1"L x .20"W	Fir tree	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.75	UL 94 V-2	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	Yes
HT-157-00120	50	25 mm Offset	9.1"L x .20"W	Fir tree	7.6 - 8.4 mm	0.75	UL 94 V-2	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	Yes
HT-157-00168	50	25mm Offset	9.1"L x .20"W	Fir tree	7.6 - 8.4 mm	0.75	-	-40°F to +266°F (-40°C to +130°C)	PA46, Brown	No	Yes
HT-157-00426	50	25mm Offset	9.2"L x .19"W	Fir tree	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.75	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	No
HT-157-00427	50	25mm Offset	9.2"L x .19"W	Fir tree	6.1 - 6.9 mm	0.75	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black, 100/pkg	Yes	No
HT-157-00221	50	25mm Offset	9.3"L x .20"W	Fir tree for oval holes	6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 13.0 mm 6.5 x 12.5 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00164	50	25 mm Offset/90° Angle	9.4"L x .20"W	Fir tree for round holes	6.1 - 7.0 mm 6.35 mm (hexagonal)	0.75	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00195	50	25 mm Offset, FT6	9.7"L x .20"W	Fir tree for round holes	6.1 - 6.9 mm	0.75	-	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes