

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Oval Fir Tree Cable Ties

Part #	Strength (Imperial)	Dimensions (L x W)	Fixation Method	Mounting Hole Dia. (Metric)	Disc Dia. (Imperial)	Flammability	Operating Temp.	Material, Color	UV Resistant	Reach Com- pliant (Art. 33)
HT-157-00288	50	9"L x 0.18"W	Fir Tree for oval holes	6.5 x 13.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm 7.0 x 12.0 mm	0.69 x 0.93	UL 94 V-2	-40°F to +266°F (-40°C to +130°C)	PA46, Brown	No	No
HT-157-00222	50	9"L x .19"W	Fir Tree for oval holes	7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm 6.5 x 12.5 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00205	50	9"L x .19"W	Fir tree for oval holes	6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm	0.69 x 0.93	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	Yes
HT-157-00333	50	9"L x .18"W	Fir tree for oval holes	6.5 x 12.5 mm 6.2 x 12.2 mm 6.5 x 13.0 mm 7.0 x 12.0 mm	0.69 x 0.93	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Black	No	Yes
HT-157-00232	50	8.6"L x .20"W	Fir tree for oval holes	6.5 x 12.5 mm 6.5 x 13.0 mm 6.2 x 12.2 mm 7.0 x 12.0 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00153	50	8.6"L x .20"W	Fir tree for oval hole	6.5 x 13.0 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm	0.69 x 0.93	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Gray	No	Yes
HT-157-00157	50	8.6"L x .20"W	Fir tree for oval holes	6.5 x 13.0 mm 7.0 x 12.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm	0.69 x 0.93	UL 94 V-2	-40°F to +266°F (-40°C to +130°C)	PA46, Brown	No	Yes
HT-157-00142	50	8.6"L x .20"W	Fir Tree for oval holes	6.5 x 12.5 mm 7.0 x 12.0 mm 6.5 x 13.0 mm 6.2 x 12.2 mm	0.69 x 0.93	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	PA66HIRHS, Black	No	Yes
HT-157-00268	50	8.5"L x .18"W	Fir tree for oval holes	7.0 x 12.0 mm 6.5 x 12.5 mm 6.5 x 13.0 mm 6.2 x 12.2 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes

Part #	Strength (Imperial)	Dimensions (L x W)	Fixation Method	Mounting Hole Dia. (Metric)	Disc Dia. (Imperial)	Flammability	Operating Temp.	Material, Color	UV Resistant	Reach Com- pliant (Art. 33)
HT-157-00069	45	6.5"L x .18"W	Fir tree for oval holes	6.2 x 12.2 mm	0.63 x 0.83	UL 94 V-2	-40°F to +275°F (-40°C to +135°C)	PA46, Gray	No	Yes
HT-157-00014	50	6.5"L x .18"W	Fir tree for oval holes	6.2 x 12.2 mm	0.63 x 0.83	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	PA66HS, Black/td>	No	Yes
HT-157-00184	50	6.5"L x .18"W	Fir tree for oval holes	6.5 x 13.0 mm	0.63 x 0.83	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	PA66HS, Black	No	No
HT-157-00053	50	6.5"L x .2"W	Fir tree for oval holes	7.0 x 12.0 mm	0.60 x 0.80	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	Yes
HT-157-00143	50	6.6"L x .20"W	Fir tree for oval holes	6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm	0.69 x 0.93	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Black	No	Yes
HT-157-00154	50	6.6"L x .20"W	Fir tree for oval holes	6.5 x 13.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm 7.0 x 12.0 mm	0.69 x 0.93	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	PA66HS, Gray	No	Yes
HT-157-00218	50	9.1"L x .20"W	Fir tree for oval holes	6.5 x 12.5 mm 7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00219	50	9.6"L x .20"W	Fir tree for oval holes	6.5 x 12.5 mm 6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 13.0 mm	0.69 x 0.93	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes
HT-157-00379	50	6.5"L x .18"W	Fir tree for oval hole	7.0 x 12.0 mm 6.5 x 13.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm	-	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	PA66HIRHSUV, Black	Yes	Yes