

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Push-Button Cable Tie Mount

Part #	Description	Hole Dia.	Max Panel Thickness	Max Tie Width	Material, Color, Qty.	Flammability	Operating Temp.	UV Resistant	Reach Compliant (Art 33.)
HT-PBM0C2	Push-Button Cable Tie Mount	0.25 - 0.29	0.12" Max Panel	0.2" Max Tie Width	PA66, Black, 100/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-PBM0M4	Push-Button Cable Tie Mount	0.25 - 0.29	0.12" Max Panel	0.2" Max Tie Width	PA66, Black, 1000/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-PBM10C2	Push-Button Cable Tie Mount	0.25 - 0.29	0.12" Max Panel	0.2" Max Tie Width	PA66, White, 100/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-PBM10M4	Push-Button Cable Tie Mount	0.25 - 0.29	0.12" Max Panel	0.2" Max Tie Width	PA66, White, 1000/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-PBM9C2	Push-Button Cable Tie Mount	0.25 - 0.29	0.12" Max Panel	0.2" Max Tie Width	PA66, Natural, 100/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-TM1SF0C2	Push-Button Cable Tie Mount	0.25 - 0.28	0.13" Max Panel	0.2" Max Tie Width	PA66, Black, 100/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-TM1SF0M4	Push-Button Cable Tie Mount	0.25 - 0.28	0.13" Max Panel	0.2" Max Tie Width	PA66, Black, 1000/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-TM1SF10C2	Push-Button Cable Tie Mount	0.25 - 0.28	0.13" Max Panel	0.2" Max Tie Width	PA66, White, 100/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-TM1S-F10M4	Push-Button Cable Tie Mount	0.25 - 0.28	0.13" Max Panel	0.2" Max Tie Width	PA66, White, 1000/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-TM1SF9M4	Push-Button Cable Tie Mount	0.25 - 0.28	0.13" Max Panel	0.2" Max Tie Width	PA66, Natural, 1000/pkg	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No