

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Push Mount Ties - Arrowhead Mount

Part #	Description	Length	Material	Color, Qty.	Reach Compliant (Art. 33)	UV Resistant	Flammability	Operating Temp.	Certs & Specs
HT-126-00245	1-Piece Cable Tie/ Arrowhead Mount with Seal	6.5" Long, 50lb Tensile	PA66HS	Natural, 4000/carton	No	No	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	-
HT-156-00444	1-Pc Cable Tie/ Arrowhead Mount with Seal	8.5" Long, 50lb Tensile	PA66HIRHS	Natural, 500/bag	Yes	No	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	-
HT-126-00080	Push Mount Tie with Seal	6.2" Long, Mounting Hole Diameter 0.24"-0.48"	PA66HS	Black, 500/pkg	Yes	No	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	-
HT-126-00076	Push Mount Tie	6.0" Long, 50lb Tensile	PA66HS	Natural, 500/pkg	Yes	No	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	-
HT-126-00186	Push Mount Tie with Seal	6.2" Long, Mounting Hole Diameter 0.26"-0.51"	PA66HS	Black, 500/pkg	Yes	No	-	-40°F to +221°F (-40°C to +105°C)	-
HT-156-00456	2-Piece Cable Tie/ Arrowhead Mount	7.9"L, 0.25 - 0.26" Mounting Hole	PA46/PEEK	Gray/Bge, 100/pkg	Yes	No	UL 94 V-2	-40°F to +302°F (-40°C to +150°C)	-
HT-115-06960	1-Pc Cable Tie/ Arrowhead Mount	9.0"L, 2.0" Bundle Diameter	PA66	Black, 1000/pkg	Yes	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	-
HT-T30RSF9C2	1-Piece Cable Tie/ Arrowhead Mount	6.3"L, 30lb, 0.04"-0.09" Panel Thickness	PA66	Natural, 100/pkg	Yes	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	UL csa-C22.2 no. 18.5 UL csa-C22.2 no. 62275 UL ANSI/UL 746B UL ANSI/UL 1565 UL ANSI/UL 62275
HT-T30RSF9M4	1-Piece Cable Tie/ Arrowhead Mount	6.3"L, 30lb, 0.04"-0.09" Panel Thickness	PA66	Natural, 1000/pkg	Yes	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	UL-ZODZ2. E64139
HT-T30RSF0C2	1-Piece Cable Tie/ Arrowhead Mount	6.3"L, 30lb, 0.04"-0.09" Panel Thickness	PA66HS	Black, 100/pkg	No	No	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	UL-ZODZ2. E64139
HT-T30RSF0M4	1-Piece Cable Tie/ Arrowhead Mount	6.3"L, 30lb, 0.04"-0.09" Panel Thickness	PA66HS	Black, 1000/pkg	No	No	UL 94 V-2	-40°F to +221°F (-40°C to +105°C)	UL-ZODZ2. E64139

Part #	Description	Length	Material	Color, Qty.	Reach Compliant (Art. 33)	UV Resistant	Flammability	Operating Temp.	Certs & Specs
HT-126-00043	1-Pc Cable Tie/ Arrowhead Mount	6"L, 50lb, 0.04"–0.14" Panel Thickness	PA66	Natural, 100/pkg	No	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	-
HT-126-00044	1-Pc Cable Tie/ Arrowhead Mount	6"L, 50lb, 0.04"–0.14" Panel Thickness	PA66	Natural, 1000/pkg	No	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	-
HT-126-00045	1-Pc Cable Tie/ Arrowhead Mount	6"L, 50lb, 0.04"–0.14" Panel Thickness	PA66	Black, 100/ pkg	No	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	-
HT-126-00046	1-Pc Cable Tie/ Arrowhead Mount	6"L, 50lb, 0.04"–0.14" Panel Thickness	PA66	Black, 1000/ pkg	No	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	-
HT-T50RSF9C2	1-Pc Cable Tie/ Arrowhead Mount	8.3"L, 50lb, 0.04"–0.14" Panel Thickness	PA66	Natural, 100/pkg	Yes	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	-
HT-T50RSF9M4	1-Pc Cable Tie/ Arrowhead Mount	8.3"L, 50lb, 0.04"–0.14" Panel Thickness	PA66	Natural, 1000/pkg	No	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	UL-ZODZ2. E64139
HT-T50RSF0C2	1-Pc Cable Tie/ Arrowhead Mount	8.3"L, 50lb, 0.04"–0.14" Panel Thickness	PA66	Black, 100/ pkg	No	No	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	UL-ZODZ2. E64139
HT-T50RSF0M4	1-Pc Cable Tie/ Arrowhead Mount	8.3"L, 50lb, 0.04"–0.14" Panel Thickness	PA66HS	Black, 1000/ pkg	No	No	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	UL-ZODZ2. E64139