

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Ratchet P-Clamp Accessories

| Part # HT-151-01529 | |
|------------------------------|--|
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Flammability | UL 94 HB |
| Operating Temp. | -40°F to +221°F |
| Reach Compliant (Article 33) | Yes |
| UV Resistant | Yes |
| Part # HT-151-01530 | |
| Material | Thermoplastic Elastomer (TPE) |
| Flammability | UL 94 HB |
| Operating Temp. | -40°F to +194°F |
| Reach Compliant (Article 33) | Yes |
| UV Resistant | Yes |
| Bundle Diameter (Imperial) | 0.13-0.42 |
| Part # HT-151-01531 | |
| Material | Thermoplastic Elastomer (TPE) |
| Flammability | UL 94 HB |
| Operating Temp. | -40°F to +194°F |
| Reach Compliant (Article 33) | Yes |
| UV Resistant | Yes |
| Bundle Diameter (Imperial) | 0.34-0.61 |
| Part # HT-151-01532 | |
| Material | Thermoplastic Elastomer (TPE) |
| Flammability | UL 94 HB |
| Operating Temp. | -40°F to +194°F |
| Reach Compliant (Article 33) | Yes |
| UV Resistant | Yes |
| Bundle Diameter (Imperial) | 0.51-1.26 |

| Part # | HT-151-01533 |
|------------------------------|-------------------------------|
| Material | Thermoplastic Elastomer (TPE) |
| Flammability | UL 94 HB |
| Operating Temp. | -40°F to +194°F |
| Reach Compliant (Article 33) | Yes |
| UV Resistant | Yes |
| Bundle Diameter (Imperial) | 1.26-1.85 |