

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Ratchet P-Clamp Size B Stainless Steel

0.52 - 0.77" Bundle Diameter 15° Short P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	4.55
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.52 - 0.77" Bundle Diameter 30° Long P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	5.93
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.52 - 0.77" Bundle Diameter 30° Short P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	4.47
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.52 - 0.77" Bundle Diameter 90° Long P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	5.11
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.52 - 0.77" Bundle Diameter 90° Short P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	4.01
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.52 - 0.77" Bundle Diameter 180° Long P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.58
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.52 - 0.77" Bundle Diameter 180° Medium P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	5.44
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.52 - 0.77" Bundle Diameter 180° Short P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	4.57
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes