

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Ratchet P-Clamp Size C

0.76 - 1.42" Bundle Diameter 15° Short P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.12
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Zinc plated (ZN) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Steel (ST)
Halogen Free	Yes
Reach Compliant (Article 33)	Yes
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 30° Long P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	7.49
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Zinc plated (ZN) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Steel (ST)
Halogen Free	Yes
Reach Compliant (Article 33)	Yes
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 30° Short P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.04
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Zinc plated (ZN) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Steel (ST)
Halogen Free	Yes
Reach Compliant (Article 33)	Yes
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 90° Long P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.69
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Zinc plated (ZN) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Steel (ST)
Halogen Free	Yes
Reach Compliant (Article 33)	Yes
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 90° Short P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	5.58
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Zinc plated (ZN) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Steel (ST)
Halogen Free	Yes
Reach Compliant (Article 33)	Yes
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 180° Long P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	8.15
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Zinc plated (ZN) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Steel (ST)
Halogen Free	Yes
Reach Compliant (Article 33)	Yes
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 180° Medium P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	7.01
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Zinc plated (ZN) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Steel (ST)
Halogen Free	Yes
Reach Compliant (Article 33)	Yes
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 180° Short P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.15
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Zinc plated (ZN) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Steel (ST)
Halogen Free	Yes
Reach Compliant (Article 33)	Yes
UV Resistant	Yes