

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Ratchet P-Clamp Size C Stainless Steel

0.76 - 1.42" Bundle Diameter 15° Short P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.12
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 30° Long P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	7.49
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 30° Short P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.04
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 90° Long P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.69
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 90° Short P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	5.58
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 180° Long P-Clamps

Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	8.15
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 180° Medium P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	7.01
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes

0.76 - 1.42" Bundle Diameter 180° Short P-Clamps	
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	6.15
Width W (Imperial)	1.37
Cable Tie Width Max (Imperial)	0.52
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F
Fixation Method	Screw Mounting
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Halogen Free	Yes
Reach Compliant (Article 33)	No
UV Resistant	Yes