

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Rubber Adhesive Cable Tie Mount

Part #	Dimensions	Material, Color, Qty.	Cable Tie Width Max	Mounting Hole Dia. (Imperial)	Adhesive	Adhesive Temp.	Flammability	Operating Temp.	UV Resistant	Reach Compliant (Art. 33)
HT-MB2.5A0C2	0.63" x 0.63"	PA66, Black, 100/pkg	0.1	0.11	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB2.5A0M4	0.63" x 0.63"	PA66, Black, 1000/pkg	0.1	0.11	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB2.5A10C2	0.63" x 0.63"	PA66, White, 100/pkg	0.1	0.11	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB2.5A10M4	0.63" x 0.63"	PA66, White, 1000/pkg	0.1	0.11	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB3A0C2	0.75" x 0.75"	PA66, Black, 100/pkg	0.14	0.12	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB3A0M4	0.75" x 0.75"	PA66, Black, 1000/pkg	0.14	0.12	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB3A10C2	0.75" x 0.75"	PA66, White, 100/pkg	0.14	0.12	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB3A10M4	0.75" x 0.75"	PA66, White, 1000/pkg	0.14	0.12	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4A0C2	1.12" x 1.12"	PA66, Black, 100/pkg	0.18	0.18	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4A0H4	1.12" x 1.12"	PA66, Black, 500/pkg	0.18	0.18	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4A10C2	1.12" x 1.12"	PA66, White, 100/pkg	0.18	0.18	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No

Part #	Dimensions	Material, Color, Qty.	Cable Tie Width Max	Mounting Hole Dia. (Imperial)	Adhesive	Adhesive Temp.	Flammability	Operating Temp.	UV Resistant	Reach Compliant (Art. 33)
HT-MB4A10H4	1.12" x 1.12"	PA66, White, 500/pkg	0.18	0.18	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4SHA0C2	1.12" x 1.12"	PA66, Black, 100/pkg	0.18	0.15	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4SHA0H4	1.12" x 1.12"	PA66, Black, 500/pkg	0.18	0.15	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB4SHA10C2	1.12" x 1.12"	PA66, White, 100/pkg	0.18	0.15	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB-4SHA10H4	1.12" x 1.12"	PA66, White, 500/pkg	0.18	0.15	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB5A0C2	1.49" x 1.49"	PA66, Black, 100/pkg	0.35	0.19	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB5A0F4	1.49" x 1.49"	PA66, Black, 250/pkg	0.35	0.19	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB5A10C2	1.49" x 1.49"	PA66, White, 100/pkg	0.35	0.19	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No
HT-MB5A10F4	1.49" x 1.49"	PA66, White, 250/pkg	0.35	0.19	Synthetic rubber with base of polyethylene foam	0°F to +150°F (-18 °C to +66 °C)	UL 94 V-2 (excluding adhesive)	-40°F to +185°F (-40°C to +85°C)	No	No