

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Saddle Mounts

Part #	Description	Bundle Dia.	Hole/Stud Dia.	Panel Thickness	Material, Color, Qty.	Flammability	Operating Temp.	UV Resistant	Reach Compliant (Art 33.)
HT-S2CM-258HIRHSH1	2-Way Saddle Mount	3.5" Max Bundle Diameter	0.25" Stud Diameter	-	PA66HIRHS, Gray, 500/pkg	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	No	Yes
HT-S2HM-250HIRHSH1	2-Way Saddle Mount	3.5" Max Bundle Diameter	0.25" Stud Diameter	-	PA66HIRHSUV, Black, 500/pkg	UL 94 HB	-40°F to +230°F (-40°C to +110°C)	Yes	Yes
HT-S3STM-500HIRHSC2	Fir Tree Saddle Mount	5.0 Bundle Dia	Hole Diameter 0.5"	Panel Thickness 0.08 - 0.52"	PA66HIRHSUV, Black, 100/pkg	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	Yes
HT-S3STM-500HIRHSF1	Fir Tree Saddle Mount	5.0 Bundle Dia	Hole Diameter 0.5"	Panel Thickness 0.08 - 0.52"	PA66HIRHSUV, Black, 250/pkg	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	Yes	No
HT-MSB-T1200HIRHSH1	Saddle Mount For Button Head Tie	1st loop; 6.0 - 2nd loop; 1.0	0.44"–0.82" Mounting Hole	Panel Thickness 0.161 - 0.752	PA66HIRHSUV, Black, 500/pkg	UL 94 HB	-40°F to +221°F (-40°C to +105°C)	No	Yes