

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Screw Mount Ties

Part #	Description	Length /Size	Max Bundle Dia.	Strength (Imperial)	Material, Color, Qty.	Fixation Method	Mounting Hole Dia. (Imperial)	Flammability	Operating Temp.	UV Resist	Reach Compliant (Art 33.)
HT-T18MR0C2	1-Pc Cable Tie/ Screw Mount	4.3" Long, #4 Screw	0.79" Max Bundle Dia	18lb	PA66HS, Black, 100/ pkg	Fixing Hole	0.12	UL 94 V-2	-40°F to +257°F (-40°C to +125°C)	No	No
HT-T18MR0M4	1-Pc Cable Tie/ Screw Mount	4.3" Long, #4 Screw	0.79" Max Bundle Dia	18lb	PA66, Black, 1000/pkg	Fixing Hole	0.12	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-T18MR9C2	1-Pc Cable Tie/ Screw Mount	4.3" Long, #4 Screw	0.79" Max Bundle Dia	18lb	PA66, Natural, 100/pkg	Fixing Hole	0.12	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-T18MR9M4	1-Pc Cable Tie/ Screw Mount	4.3" Long, #4 Screw	0.79" Max Bundle Dia	18lb	PA66, Natural, 1000/pkg	Fixing Hole	0.12	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-T30MR0C2	1-Pc Cable Tie/ Screw Mount	6.3" Long, #8 Screw	1.3" Max Bun- dle Dia	30lb	PA66, Black, 100/pkg	Fixing Hole	0.17	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	Yes
HT-T30MR0M4	1-Pc Cable Tie/ Screw Mount	6.3" Long, #8 Screw	1.3" Max Bun- dle Dia	30lb	PA66, Black, 1000/pkg	Fixing Hole	0.17	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No
HT-T30MR9C2	1-Pc Cable Tie/ Screw Mount	6.3" Long, #8 Screw	1.3" Max Bun- dle Dia	30lb	PA66, Natural, 100/pkg	Fixing Hole	0.17	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	Yes
HT-T30MR9M4	1-Pc Cable Tie/ Screw Mount	6.3" Long, #8 Screw	1.3" Max Bun- dle Dia	30lb	PA66, Natural, 1000/pkg	Fixing Hole	0.17	UL 94 V-2	-40°F to +185°F (-40°C to +85°C)	No	No

Part #	Description	Dimensions	Bundle Dia. (Imperial)	Strength	Material, Color	Qty.	Flamma- bility	UV Resist.	Operating Temp.	Reach Compliant (Art 33.)
HT-T50MR0C2	1-Pc Cable Tie/ Screw Mount	8.5" Long, #10 Screw	0.06" - 1.8"	50lb Tensile Strength	PA66, Black	100/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50MR0HSM4	1-Pc Cable Tie/ Screw Mount	8.5" Long, #10 Screw	0.06" - 1.8"	50lb Tensile Strength	PA66HS, Black	1000/pkg	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No
HT-T50M-R0M4	1-Pc Cable Tie/ Screw Mount	8.5" Long, #10 Screw	0.06" - 1.8"	50lb Tensile Strength	PA66, Black	1000/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50MR9C2	1-Pc Cable Tie/ Screw Mount	8.5" Long, #10 Screw	0.06" - 1.8"	50lb Tensile Strength	PA66, Nat- ural	100/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50M-R9M4	1-Pc Cable Tie/ Screw Mount	8.5" Long, #10 Screw	0.06" - 1.8"	50lb Tensile Strength	PA66, Nat- ural	1000/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50MR9X2	1-Pc Cable Tie/ Screw Mount	8.5" Long, #10 Screw	0.06" - 1.8"	50lb Tensile Strength	PA66, Nat- ural	25/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-113-00060	1-Pc Cable Tie/ Screw Mount	8.5" Long, 0.2" Hole	0.06" - 1.8"	50lb Tensile Strength	PA66HS, Black	100/pkg	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No
HT-113-00061	1-Pc Cable Tie/ Screw Mount	8.5" Long, 0.2" Hole	0.06" - 1.8"	50lb Tensile Strength	PA66HS, Black	1000/pkg	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No
HT-T50MI0C2	1-Pc Cable Tie/ Screw Mount	12.4" Long, #10 Screw	0.06" - 3.4"	50lb Tensile Strength	PA66, Black	100/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50MI0M4	1-Pc Cable Tie/ Screw Mount	12.4" Long, #10 Screw	0.06" - 3.4"	50lb Tensile Strength	PA66, Black	1000/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50MI9C2	1-Pc Cable Tie/ Screw Mount	12.4" Long, #10 Screw	0.06" - 3.4"	50lb Tensile Strength	PA66, Nat- ural	100/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50MI9M4	1-Pc Cable Tie/ Screw Mount	12.4" Long, #10 Screw	0.06" - 3.4"	50lb Tensile Strength	PA66, Black	1000/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50ML0C2	1-Pc Cable Tie/ Screw Mount	15.4" Long, #10 Screw	0.12" - 4.0"	50lb Tensile Strength	PA66, Black	100/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50M-L0M4	1-Pc Cable Tie/ Screw Mount	15.4" Long, #10 Screw	0.12" - 4.0"	50lb Tensile Strength	PA66, Black	1000/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T50ML9C2	1-Pc Cable Tie/ Screw Mount	15.4" Long, #10 Screw	0.12" - 4.0"	50lb Tensile Strength	PA66, Nat- ural	100/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes
HT-T50M-L9M4	1-Pc Cable Tie/ Screw Mount	15.4" Long, #10 Screw	0.12" - 4.0"	50lb Tensile Strength	PA66, Nat- ural	1000/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	No
HT-T120MR0H4	1-Pc Cable Tie/ Screw Mount	15.6" L, 0.25" Hole	0.20" - 4.02"	120lb Tensile Strength	PA66, Black	500/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes
HT-T120MR0HSH4	1-Pc Cable Tie/ Screw Mount	15.6" L, 0.25" Hole	0.20" - 4.02"	120lb Tensile Strength	PA66HS, Black	500/pkg	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	Yes

Part #	Description	Dimensions	Bundle Dia. (Imperial)	Strength	Material, Color	Qty.	Flamma- bility	UV Resist.	Operating Temp.	Reach Compliant (Art 33.)
HT-T120M- R0K2	1-Pc Cable Tie/ Screw Mount	15.6" L, 0.25" Hole	0.20" - 4.02"	120lb Tensile Strength	PA66, Black	50/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes
HT-T120M- R0UVK2	1-Pc Cable Tie/ Screw Mount	15.6" L, 0.25" Hole	0.20" - 4.02"	120lb Tensile Strength	PA66UV, Black	50/pkg	UL 94 HB	Yes	-40°F to +185°F (-40°C to +85°C)	Yes
HT- T120MR9H4	1-Pc Cable Tie/ Screw Mount	15.6" L, 0.25" Hole	0.20" - 4.02"	120lb Tensile Strength	PA66, Nat- ural	500/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes
HT-T120M- R9K2	1-Pc Cable Tie/ Screw Mount	15.6" L, 0.25" Hole	0.20" - 4.02"	120lb Tensile Strength	PA66, Nat- ural	50/pkg	UL 94 V-2	No	-40°F to +185°F (-40°C to +85°C)	Yes