

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Self-Laminating Tags

Part #	Description	Dimensions	Color, Qty.	Halogen Free	UV Resistant	Operating Temp.	Adhesive	Adhesive Temp.	Reach Compliant
HT-CT0753X2	Self-Laminating Tag, Generic Write-On, Blank Lines	3.0" x .75"	Orange, 25/pkg	No	No	-40°F to +257°F (-40°C to +125°C)	Acrylic	-40°F to +302°F (-40°C to +150°C)	Yes
HT-CT1503X2	Self-Laminating Tag, Generic Write-On, Blank Lines	4.0" x 1.5"	Orange, 25/pkg	No	No	-40°F to +257°F (-40°C to +125°C)	Acrylic	-40°F to +300°F (-40°C to +149°C)	Yes
HT-CT2003X2	Self-Laminating Tag, Caution Write-On, Fiber Optic Cable	3.5" x 2.0"	Orange, 25/pkg	No	No	-40°F to +257°F (-40°C to +125°C)	Acrylic	-40°F to +302°F (-40°C to +150°C)	Yes
HT-CT2012X2	Self-Laminating Tag, Caution Write-On, Telephone Cable	3.5" x 2.0"	Yellow, 25/pkg	No	No	-40°F to +257°F (-40°C to +125°C)	Acrylic	-40°F to +302°F (-40°C to +150°C)	Yes
HT-CTA0753X2	Self-Laminating Tag, Adhesive, Generic Write-On, Blank Lines	3.0" x .75"	Orange, 25/pkg	No	No	-40°F to +257°F (-40°C to +125°C)	Acrylic	-40°F to +302°F (-40°C to +150°C)	No
HT-CTA1503X2	Self-Laminating Tag, Adhesive, Generic Write-On, Blank Lines	4.0" x 1.5"	Orange, 25/pkg	No	No	-40°F to +257°F (-40°C to +125°C)	Acrylic	-40°F to +302°F (-40°C to +150°C)	No