

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Special Materials Cable Ties

Part #	Description	Length	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art 33.)	Certs & Specs
HT-118-00032	High-Temp Cable Tie	5.7" Long	52lb Tensile Strength	PEEK, Beige, 100/pkg	0.16 - 1.4	UL 94 V-0 (3 mm)	No	-67°F to +464°F (-55°C to +240°C)	Yes	DNV GL EN 62275:2009 IEC EN 62275
HT-111-01235	High-Temp Cable Tie	8.7" Long	85lb Tensile Strength	PEEK, Beige, 100/pkg	0.32 - 2.2	UL 94 V-0	No	-67°F to +464°F (-55°C to +240°C)	Yes	Lloyd's Register IEC 62275 DNV GL EN 62275:2009 IEC EN 62275
HT-118-00116	High-Temp Cable Tie	9.8" Long	67lb Tensile Strength	PEEK, Beige, 100/pkg	0.16 - 2.6	UL 94 V-0 (3 mm)	No	-67°F to +464°F (-55°C to +240°C)	Yes	-
HT-111-01670	High-Temp Cable Tie	5.9" Long	100lb Tensile Strength	PAEK, Beige, 100/pkg	0.06 - 1.38	UL 94 V-0	No	-67°F to +392°F (-55°C to +200°C)	No	-
HT-111-01699	High-Temp Cable Tie	7.9" Long	100lb Tensile Strength	PAEK, Beige, 100/pkg	0.06 - 2.0	UL 94 V-0	No	-67°F to +392°F (-55°C to +200°C)	No	-
HT-T18S0HSM4	High-Temp Cable Tie	3.3" Long, UL Rated	18lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 0.63	UL 94 V-2	No	-40°F to +221°F (-40°C to +105°C)	No	UL csa-C22.2 no. 62275 UL ANSI/UL 62275
HT-T18R0H-SC2	High-Temp Cable Tie	4" Long, UL Rated	18lb Tensile Strength	PA66HS, Black, 100/pkg	0.06 - 0.87	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T18R0HSM4	High-Temp Cable Tie	4" Long, UL Rated	18lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 0.87	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T18R0H-SUVM4	High-Temp Cable Tie	4" Long	18lb Tensile Strength	PA66HSUV, Black, 1000/pkg	0.06 - 0.87	UL 94 HB	Yes	-40°F to +257°F (-40°C to +125°C)	No	-
HT-T18I-OHSM4	High-Temp Cable Tie	5.5" Long, UL Rated	18lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	Yes	UL 62275
HT-T18L0H-SC2	High-Temp Cable Tie	8" Long, UL Rated	18lb Tensile Strength	PA66HS, Black, 100/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275

Part #	Description	Length	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art 33.)	Certs & Specs
HT-T18L-OHSM4	High-Temp Cable Tie	8" Long, UL Rated	18lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T30R0HIRM4	High-Temp Cable Tie	6" Long, UL Rated	30lb Tensile Strength	PA66HIRH-SUV, Black, 1000/pkg	0.06 - 1.38	UL 94 HB	Yes	-40°F to +221°F (-40°C to +105°C)	No	UL-ZODZ2.E64139
HT-T30R0H-SC2	High-Temp Cable Tie	6" Long, UL Rated	30lb Tensile Strength	PA66HS, Black, 100/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T30R0HSM4	High-Temp Cable Tie	6" Long, UL Rated	30lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T30R0H-SUVM4	High-Temp Cable Tie	6" Long, UL Rated	30lb Tensile Strength	PA66HSUV, Black, 1000/pkg	0.06 - 1.38	UL 94 HB	Yes	-40°F to +257°F (-40°C to +125°C)	No	-
HT-T30R9HSM4	High-Temp Cable Tie	6" Long, UL Rated	30lb Tensile Strength	PA66HS, Natural, 1000/pkg	0.06 - 1.38	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T30L-OHSM4	High-Temp Cable Tie	8" Long, UL Rated	30lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T30LL-OHSM4	High-Temp Cable Tie	11" Long	30lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T40R0HSM4	High-Temp Cable Tie	8" Long, UL Rated	40lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 2.17	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T40L0H-SC2	High-Temp Cable Tie	14" Long, UL Rated	40lb Tensile Strength	PA66HS, Black, 100/pkg	0.06 - 4.13	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T50R0HIRM4	High-Temp Cable Tie	8" Long, UL Rated	50lb Tensile Strength	PA66HIRH-SUV, Black, 1000/pkg	0.06 - 1.97	UL 94 HB	Yes	-40°F to +221°F (-40°C to +105°C)	No	-
HT-T50R0H-SC2	High-Temp Cable Tie	8" Long, UL Rated	50lb Tensile Strength	PA66HS, Black, 100/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T50R0HSM4	High-Temp Cable Tie	8" Long, UL Rated	50lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	Yes	UL 62275

Part #	Description	Length	Strength	Material, Color, Qty.	Bundle Dia. (Imperial)	Flammability	UV Resistant	Operating Temp.	Reach Compliant (Art 33.)	Certs & Specs
HT-T50R0H-SUVM4	High-Temp Cable Tie	8" Long, UL Rated	50lb Tensile Strength	PA66HSUV, Black, 1000/pkg	0.06 - 1.97	UL 94 HB	Yes	-40°F to +257°F (-40°C to +125°C)	No	-
HT-T50R9HSM4	High-Temp Cable Tie	8" Long, UL Rated	50lb Tensile Strength	PA66HS, Natural, 1000/pkg	0.06 - 1.97	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T50I0HSC2	High-Temp Cable Tie	12" Long, UL Rated	50lb Tensile Strength	PA66HS, Black, 100/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T50I-0HSM4	High-Temp Cable Tie	12" Long, UL Rated	50lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 3.15	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T50I0HSU-VM4	High-Temp Cable Tie	12" Long, UL Rated	50lb Tensile Strength	PA66HSUV, Black, 1000/pkg	0.06 - 3.15	UL 94 HB	Yes	-40°F to +257°F (-40°C to +125°C)	No	-
HT-T50L0H-SC2	High-Temp Cable Tie	15" Long, UL Rated	50lb Tensile Strength	PA66HS, Black, 100/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T50L-0HSM4	High-Temp Cable Tie	15" Long, UL Rated	50lb Tensile Strength	PA66HS, Black, 1000/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T50L0H-SUVM4	High-Temp Cable Tie	15" Long, UL Rated	50lb Tensile Strength	PA66HSUV, Black, 1000/pkg	0.06 - 4.33	UL 94 HB	Yes	-40°F to +257°F (-40°C to +125°C)	Yes	-
HT-T50L1STN-LM4	High-Temp Cable Tie	15" Long	50lb Tensile Strength	PA46, Brown, 1000/pkg	0.06 - 4.33	UL 94 V-2	No	-40°F to +266°F (-40°C to +130°C)	Yes	-
HT-T120S0HSH4	Heavy Duty Cable Tie	9" Long, UL Rated	120lb Tensile Strength	PA66HS, Black, 500/pkg	0.20 - 2.17	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	Yes	UL 62275
HT-T120R0HSH4	High-Temp Cable Tie	15" Long, UL Rated	120lb Tensile Strength	PA66HS, Black, 500/pkg	0.20 - 4.13	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275
HT-T120R0HSK2	High-Temp Cable Tie	15" Long, UL Rated	120lb Tensile Strength	PA66HS, Black, 50/pkg	0.20 - 4.13	UL 94 V-2	No	-40°F to +257°F (-40°C to +125°C)	No	UL 62275