

PRODUCT SPECIFICATION SHEET

Product Name: HellermannTyton® Spiralwrap Protective Sheathing & Metal-Content Wrap

Part#	Description	Diameter	Material, Color, Qt.	Bundle Diameter (Imperial)	Flammability	Operating Temp.	Halogen Free	UV Resist	Reach Compliant (Article 33)
HT-3FRP0C	Protective Sheathing	0.5"	PE-FR, Black, 100 ft/roll	0.37 - 4.0	UL 94 V-2	-4°F to +176°F (-20°C to +80°C)	No	No	Yes
HT-3FRP9C	Protective Sheathing	0.5"	PE-FR, Natural, 100 ft/roll	0.37 - 4.0	UL 94 V-2	-4°F to +176°F (-20°C to +80°C)	No	No	Yes
HT-3N0C	Protective Sheathing	0.5"	PA6, Black, 100 ft/roll	0.37 - 4.0	UL 94 HB	-40°F to +250°F (-40°C to +121°C)	Yes	No	Yes
HT-3N9C	Protective Sheathing	0.5"	PA6, Natural, 100 ft/roll	0.37 - 4.0	UL 94 HB	-40°F to +250°F (-40°C to +121°C)	Yes	No	Yes
HT-3NFP0C	Protective Sheathing	0.5"	PE, Black, 100 ft/roll	0.37 - 4.0	-	-76°F to +190°F (-60°C to +88°C)	No	No	Yes
HT-3NFP9C	Protective Sheathing	0.5"	PE, Natural, 100 ft/roll	0.37 - 4.0	-	-76°F to +190°F (-60°C to +88°C)	Yes	No	Yes
HT-3P9C	Protective Sheathing	0.5"	PTFE, Natural, 100 ft/roll	0.37 - 3.0	UL 94 V-0	-449°F to +500°F (-267°C to +260°C)	No	No	Yes
HT-4FRP0C	Protective Sheathing	0.75"	PE-FR, Black, 100 ft/roll	0.75 - 5.0	UL 94 V-2	-4°F to +176°F (-20°C to +80°C)	No	No	Yes
HT-4FRP9C	Protective Sheathing	0.75"	PE-FR, Natural, 100 ft/roll	0.75 - 5.0	UL 94 V-2	-4°F to +176°F (-20°C to +80°C)	No	No	Yes
HT-4N0C	Protective Sheathing	0.75"	PA6, Black, 100 ft/roll	0.5 - 5.0	UL 94 HB	-40°F to +250°F (-40°C to +121°C)	Yes	No	Yes
HT-4N9C	Protective Sheathing	0.75"	PA6, Natural, 100 ft/roll	0.5 - 5.0	UL 94 HB	-40°F to +250°F (-40°C to +121°C)	Yes	No	Yes
HT-4NFP0C	Protective Sheathing	0.75"	PE, Black, 100 ft/roll	0.75 - 5.0	-	-76°F to +190°F (-60°C to +88°C)	No	No	Yes
HT-4NFP9C	Protective Sheathing	0.75"	PE, Natural, 100 ft/roll	0.75 - 5.0	-	-76°F to +190°F (-60°C to +88°C)	Yes	No	Yes
HT-4P9C	Protective Sheathing	0.75"	PTFE, Natural, 100 ft/roll	0.5 - 4.0	UL 94 V-0	-449°F to +500°F (-267°C to +260°C)	No	No	Yes
HT-161-05088	Protective Sheathing	0.88"	Polyamide, Black, 500ft/roll	0.5 - 5.0	-	-40°F to +250°F (-40°C to +121°C)	Yes	No	Yes

Part#	Description	Diameter	Material, Color, Qt.	Bundle Diameter (Imperial)	Flammability	Operating Temp.	Halogen Free	UV Resist	Reach Compliant (Article 33)
HT-161-05089	Protective Sheathing	0.75"	PA6, Black, 500ft/roll	0.5 - 5.0	UL 94 HB	-40°F to +250°F (-40°C to +121°C)	Yes	No	Yes
HT-161-05090	Protective Sheathing	0.38"	PE, Black, 500ft/roll	0.31 - 3.0	-	-76°F to +190°F (-60°C to +88°C)	-	No	No
HT-161-05084	Protective Sheathing	1"	PE-FR, Black, 100 ft/roll	1.0 - 7.0	UL 94 V-2	-4°F to +176°F (-20°C to +80°C)	No	No	Yes
HT-5FRP9C	Protective Sheathing	1"	PE-FR, Natural, 100 ft/roll	1.0 - 7.0	UL 94 V-2	-4°F to +176°F (-20°C to +80°C)	No	No	Yes
HT-5N0C	Protective Sheathing	1"	PA6, Black, 100 ft/roll	1.0 - 7.0	-	-40°F to +250°F (-40°C to +121°C)	Yes	No	Yes
HT-5N9C	Protective Sheathing	1"	PA6, Natural, 100 ft/roll	1.0 - 7.0	-	-40°F to +250°F (-40°C to +121°C)	Yes	No	Yes
HT-5NFP0C	Protective Sheathing	1"	PE, Black, 100 ft/roll	1.0 - 7.0	-	-76°F to +190°F (-60°C to +88°C)	No	No	Yes
HT-5NFP9C	Protective Sheathing	1"	PE, Natural, 100 ft/roll	1.0 - 7.0	-	-76°F to +190°F (-60°C to +88°C)	Yes	No	Yes
HT-5P9C	Protective Sheathing	1"	PTFE, Natural, 100 ft/roll	0.75 - 5.0	UL 94 V-0	-449°F to +500°F (-267°C to +260°C)	No	No	Yes
HT-161-46000	Spiralwrap Metal-Content	0.06"	PE/SS, Blue, 98 ft/roll	0.06 - 0.31	UL 94 HB	-76°F to +176°F (-60°C to +80°C)	Yes	No	Yes
HT-161-46100	Spiralwrap Metal-Content	0.16"	PE/SS, Blue, 98 ft/roll	0.20 - 0.79	UL 94 HB	-76°F to +176°F (-60°C to +80°C)	Yes	No	Yes
HT-161-46200	Spiralwrap Metal-Content	0.35"	PE/SS, Blue, 98 ft/roll	0.39 - 3.94	UL 94 HB	-76°F to +176°F (-60°C to +80°C)	Yes	No	Yes
HT-161-46300	Spiralwrap Metal-Content	0.63"	PE/SS, Blue, 98 ft/roll	0.79 - 5.91	UL 94 HB	-76°F to +176°F (-60°C to +80°C)	Yes	No	Yes