

# PRODUCT SPECIFICATION SHEET

**Product Name: HellermannTyton® UV Resistant Cable Ties**

| Part #       | Descriptions           | Length   | Strength              | Material, Color, Qty.   | Bundle Dia. (Imperial) | Flammability | Operating Temp.                  | UV Resistant | Reach Compliant (Art. 33) |
|--------------|------------------------|----------|-----------------------|-------------------------|------------------------|--------------|----------------------------------|--------------|---------------------------|
| HT-T18R0UVC2 | UV Resistant Cable Tie | 4" Long  | 18lb Tensile Strength | PA66UV, Black, 100/pkg  | 0.06 - 0.87            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | Yes                       |
| HT-T18R0UVM4 | UV Resistant Cable Tie | 4" Long  | 18lb Tensile Strength | PA66UV, Black, 1000/pkg | 0.06 - 0.87            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | No                        |
| HT-T30R0UVC2 | UV Resistant Cable Tie | 6" Long  | 30lb Tensile Strength | PA66UV, Black, 100/pkg  | 0.06 - 1.38            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | Yes                       |
| HT-T30R0UVM4 | UV Resistant Cable Tie | 6" Long  | 30lb Tensile Strength | PA66UV, Black, 1000/pkg | 0.06 - 1.38            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | No                        |
| HT-T30L0UVC2 | UV Resistant Cable Tie | 8" Long  | 30lb Tensile Strength | PA66UV, Black, 100/pkg  | 0.06 - 1.97            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | No                        |
| HT-T50R0UVC2 | UV Resistant Cable Tie | 8" Long  | 50lb Tensile Strength | PA66UV, Black, 100/pkg  | 0.06 - 1.97            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | Yes                       |
| HT-T50R0UVM4 | UV Resistant Cable Tie | 8" Long  | 50lb Tensile Strength | PA66UV, Black, 1000/pkg | 0.06 - 1.97            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | No                        |
| HT-T50R2UVM4 | UV Resistant Cable Tie | 8" Long  | 50lb Tensile Strength | PA66UV, Red, 1000/pkg   | 0.06 - 1.97            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | No                        |
| HT-T50I0UVC2 | UV Resistant Cable Tie | 12" Long | 50lb Tensile Strength | PA66UV, Black, 100/pkg  | 0.06 - 3.15            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | Yes                       |
| HT-T50I0UVM4 | UV Resistant Cable Tie | 12" Long | 50lb Tensile Strength | PA66UV, Black, 1000/pkg | 0.06 - 3.15            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | No                        |
| HT-T50L0UVC2 | UV Resistant Cable Tie | 15" Long | 50lb Tensile Strength | PA66UV, Black, 100/pkg  | 0.06 - 4.33            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | Yes                       |
| HT-T50L0UVM4 | UV Resistant Cable Tie | 15" Long | 50lb Tensile Strength | PA66UV, Black, 1000/pkg | 0.06 - 4.33            | UL 94 V-2    | -40°F to +185°F (-40°C to +85°C) | Yes          | No                        |