

# PRODUCT SPECIFICATION SHEET

**Product Name: HellermannTyton® Wiring Duct Cover**

| Part #       | Duct Size                       | Length    | Material, Color     | Qty.          | Flammability | UV Resistant | Operating Temp. | Reach Compliant | Certs. & Specifications                             |
|--------------|---------------------------------|-----------|---------------------|---------------|--------------|--------------|-----------------|-----------------|-----------------------------------------------------|
| HT-181-90050 | Wiring Duct Cover for 1/2" Duct | 6 ft Long | PVC, Black          | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-90051 | Wiring Duct Cover for 1/2" Duct | 6 ft Long | PVC, Gray           | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-91517 | Wiring Duct Cover for 1/2" Duct | 6 ft Long | PVC, White          | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-90750 | Wiring Duct Cover for 3/4" Duct | 6 ft Long | PVC, Gray           | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-90751 | Wiring Duct Cover for 3/4" Duct | 6 ft Long | PVC, White          | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-91000 | Wiring Duct Cover for 1" Duct   | 6 ft Long | PVC, Black          | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-91002 | Wiring Duct Cover for 1" Duct   | 6 ft Long | PVC, Intrinsic Blue | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-91003 | Wiring Duct Cover for 1" Duct   | 6 ft Long | PVC, Gray           | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |

| Part #       | Duct Size                     | Length    | Material, Color     | Qty.          | Flammability | UV Resistant | Operating Temp. | Reach Compliant | Certs. & Specifications                             |
|--------------|-------------------------------|-----------|---------------------|---------------|--------------|--------------|-----------------|-----------------|-----------------------------------------------------|
| HT-181-91004 | Wiring Duct Cover for 1" Duct | 6 ft Long | PVC, Gray           | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-91007 | Wiring Duct Cover for 1" duct | 6 ft Long | PVC, White          | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-91008 | Wiring Duct Cover for 1" Duct | 6 ft Long | PVC, White          | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-91009 | Wiring Duct Cover for 1" Duct | 7 ft Long | PVC, White          | 140 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-91010 | Wiring Duct Cover for 1" Duct | 7 ft Long | PVC, Gray           | 140 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-92001 | Wiring Duct Cover for 2" Duct | 6 ft Long | PVC, Black          | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-92003 | Wiring Duct Cover for 2" Duct | 6 ft Long | PVC, Intrinsic Blue | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-92004 | Wiring Duct Cover for 2" Duct | 6 ft Long | PVC, Gray           | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-92005 | Wiring Duct Cover for 2" Duct | 6 ft Long | PVC, Gray           | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |
| HT-181-92010 | Wiring Duct Cover for 2" Duct | 6 ft Long | PVC, White          | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013<br>CSA EN 50085-2-3_1A |

| Part #       | Duct Size                         | Length    | Material, Color | Qty.          | Flammability | UV Resistant | Operating Temp. | Reach Compliant | Certs. & Specifications                             |
|--------------|-----------------------------------|-----------|-----------------|---------------|--------------|--------------|-----------------|-----------------|-----------------------------------------------------|
| HT-181-92011 | Wiring Duct Cover for 2" Duct     | 6 ft Long | PVC, White      | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A    |
| HT-181-92015 | Wiring Duct Cover for 2" Duct     | 6 ft Long | PVC, Black      | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A    |
| HT-181-92021 | Wiring Duct Cover for 2" Duct     | 7 ft Long | PVC, White      | 140 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A    |
| HT-181-92022 | Wiring Duct Cover for 2" Duct     | 7 ft Long | PVC, Gray       | 140 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A    |
| HT-181-00260 | Wiring Duct Cover for 2-1/2" Duct | 6 ft Long | PVC, Gray       | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A<br>UL |
| HT-181-00261 | Wiring Duct Cover for 2-1/2" Duct | 6 ft Long | PVC, Gray       | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A<br>UL |
| HT-181-00262 | Wiring Duct Cover for 2-1/2" Duct | 6 ft Long | PVC, White      | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A    |
| HT-181-93000 | Wiring Duct Cover for 3" Duct     | 6 ft Long | PVC, Black      | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A    |
| HT-181-93003 | Wiring Duct Cover for 3" Duct     | 6 ft Long | PVC, Black      | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A    |

| Part #       | Duct Size                     | Length    | Material, Color     | Qty.          | Flammability | UV Resistant | Operating Temp. | Reach Compliant | Certs. & Specifications                          |
|--------------|-------------------------------|-----------|---------------------|---------------|--------------|--------------|-----------------|-----------------|--------------------------------------------------|
| HT-181-93005 | Wiring Duct Cover for 3" Duct | 6 ft Long | PVC, Intrinsic Blue | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-93007 | Wiring Duct Cover for 3" Duct | 6 ft Long | PVC, Gray           | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-93008 | Wiring Duct Cover for 3" Duct | 6 ft Long | PVC, Gray           | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-93010 | Wiring Duct Cover for 3" Duct | 6 ft Long | PVC, White          | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-93011 | Wiring Duct Cover for 3" Duct | 6 ft Long | PVC, White          | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-93023 | Wiring Duct Cover for 3" Duct | 7 ft Long | PVC, White          | 140 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-93024 | Wiring Duct Cover for 3" Duct | 7 ft Long | PVC, Gray           | 140 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-94000 | Wiring Duct Cover for 4" Duct | 6 ft Long | PVC, Black          | 30ft/box      | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-94003 | Wiring Duct Cover for 4" Duct | 6 ft Long | PVC, Black          | 120 ft/carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |

| Part #       | Duct Size                     | Length    | Material, Color     | Qty.           | Flammability | UV Resistant | Operating Temp. | Reach Compliant | Certs. & Specifications                          |
|--------------|-------------------------------|-----------|---------------------|----------------|--------------|--------------|-----------------|-----------------|--------------------------------------------------|
| T-181-94007  | Wiring Duct Cover for 4" Duct | 6 ft Long | PVC, Intrinsic Blue | 120 ft/ carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-94008 | Wiring Duct Cover for 4" Duct | 6 ft Long | PVC, Gray           | 30ft/box       | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-94009 | Wiring Duct Cover for 4" Duct | 6 ft Long | PVC, Gray           | 120 ft/ carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-94013 | Wiring Duct Cover for 4" Duct | 6 ft Long | PVC, White          | 30ft/box       | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-94014 | Wiring Duct Cover for 4" Duct | 6 ft Long | PVC, White          | 120 ft/ carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-94024 | Wiring Duct Cover for 4" Duct | 7 ft Long | PVC, Gray           | 140 ft/ carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |
| HT-181-94025 | Wiring Duct Cover for 4" Duct | 7 ft Long | PVC, White          | 140 ft/ carton | UL 94 V-0    | No           | +122°F (+50°C)  | No              | UL EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A |