

PRODUCT SPECIFICATION SHEET

Product Name: Middle Atlantic® DRK Series Cable Management Enclosures

Specifications	
Weight Capacity	Static load capacity: 10,000 lbs / UL Listed load capacity: 2,500 lbs / Seismic Certified load capacity: 815 lbs
Seismic Rated	Seismic certified to the UBC 1997 and 2001 CBC Seismic Zone 4 and the IBC 2000, IBC 2003, 2002 ASCE Standard 7 and 2003 NFPA 5000 Seismic Use Group III for protecting 815 lbs of essential equipment in upper floor installations when used in conjunction with our MA-MRK-Z4 seismic floor brackets with an IP value of 1.5
Construction	Top and bottom shall be 14-gauge steel, horizontal braces shall be 1/8" thick steel, rack rails shall be 11-gauge steel
Finish	Durable black powder coat

Part #	Panel Width	Rackrail	Racking Height	O.D Height	Useable Depth	O.D Depth	O.D Width	Weight
MA-DRK19-44-31	19"	10-32 threaded on EIA Standard spacing	77" (44 Space)	83.5"	24.25"	31.5"	30"	200 lbs
MA-DRK19-44-31K	19"	10-32 threaded on EIA Standard spacing	77" (44 Space)	83.5"	24.25"	31.5"	30"	406 lbs
MA-DRK19-44-31PRO	19"	Square hole (cage-nut style) on EIA Standard spacing	77" (44 Space)	83.5"	24.25"	31.5"	30"	200 lbs
MA-DRK19-44-36	19"	10-32 threaded on EIA Standard spacing	77" (44 Space)	83.5"	28.75"	36"	30"	220 lbs
MA-DRK19-44-36PRO	19"	Square hole (cage-nut style) on EIA Standard spacing	77" (44 Space)	83.5"	28.75"	36"	30"	280 lbs
MA-DRK19-44-42	19"	10-32 threaded on EIA Standard spacing	77" (44 Space)	83.5"	34.75"	42"	30"	250 lbs
MA-DRK19-44-42PRO	19"	Square hole (cage-nut style) on EIA Standard spacing	77" (44 Space)	83.5"	34.75"	42"	30"	250 lbs
MA-DRK23-44-31	23"	10-32 threaded on EIA Standard spacing	77" (44 Space)	83.5"	28.25"	31.5"	30"	200 lbs