

PRODUCT SPECIFICATION SHEET

Product Name: Panduit Plenum Rated Tak-Ty® Hook and Loop Cable Ties

Part #	Tak-Ty Plenum Ties		Tak-Ty Plenum Strips		
	PAN-HLTP2I	PAN-HLTP3I	PAN-HLSP1-5S	PAN-HLSP3S	PAN-HLSP5S
Quantity / Pack	10		10		
Material	Nylon Loop, Polyethylene Hook		Nylon Loop, Polyethylene Hook		
Operating Temperature	0°F to 122°F (-17°C to 50°C)		0°F to 122°F (-17°C to 50°C)		
Minimum Tensile Strength	40 lbs.		18 lbs.		
Min Bundle Diameter	0.25"		0.25"		
Max Bundle Diameter	1.91"	3.18"	1.5"	3.20"	5.0"
Length	8.0"	12.0"	6.0"	12.0"	18.0"
Width	0.5" Body and 1.0" Head		0.75"		
Thickness	0.10"		0.10"		
RoHS Compliancy Status	Compliant		Compliant		
CE Compliancy Status	Compliant		Compliant		
UL Listed	File Number E56854		No		
Flamability Rating	UL94V-2		No		
NEC	Section 300-22 (C) and (D)				
Note: Minimum 2" overlap required to achieve loop tensile rating					