

PRODUCT SPECIFICATION SHEET

Product Name: Panduit® Super-Grip™ Cable Ties

Specifications	
Material	Nylon 6.6 (Standard, Weather Resistant, or Heat-Stabilized)
Industry Standards	CSA Certified (Standard, Weather Resistant only) UL E56854 (Standard, Weather Resistant only) CE Compliant RoHS Compliant

Part #	Material	Length In. (mm)	Width In. (mm)	Thickness In. (mm)	Max Bundle Dia. In. (mm)	Min. Loop Tensile Strength Lbs. (N)	Recommended Tools	
PAN-SG200S-C0	Weather Resistant Nylon 6.6	8.3 (211)	0.225 (5.7)	0.046 (1.2)	2.00 (51)	50 (222)		
PAN-SG200S-M30	Heat-Stabilized Nylon 6.6	8.3 (211)	0.225 (5.7)	0.046 (1.2)	2.00 (51)	50 (222)		
PAN-SG250S-C	Nylon 6.6	10.4 (264)	0.225 (5.7)	0.050 (1.3)	2.60 (66)	70 (311)	GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2	
PAN-SG250S-C0	Weather Resistant Nylon 6.6	10.4 (264)	0.225 (5.7)	0.050 (1.3)	2.60 (66)	70 (311)		
PAN-SG300S-C0	Weather Resistant Nylon 6.6	12.4 (315)	0.225 (5.7)	0.050 (1.3)	3.20 (81)	70 (311)		
PAN-SG370S-C	Nylon 6.6	15.3 (389)	0.225 (5.7)	0.052 (1.3)	4.20 (107)	70 (311)		
PAN-SG350LH-L	Nylon 6.6	15.3 (389)	0.330 (8.4)	0.064 (1.6)	4.13 (105)	120 (534)		GTH, GS4H, GS4EH, PTH, STH2, ST3EH
PAN-SG350LH-L0	Weather Resistant Nylon 6.6	15.3 (389)	0.330 (8.4)	0.064 (1.6)	4.13 (105)	120 (534)		
PAN-SG350LH-TL30	Heat-Stabilized Nylon 6.6	15.3 (389)	0.330 (8.4)	0.064 (1.6)	4.13 (105)	120 (534)		