

PRODUCT SPECIFICATION SHEET

Product Name: TOWER GFCI Plugs & Extensions

Part #	ED-PD-TW-GFCI-9005	ED-PD-TW-GFCI-8018	ED-PD-TW-GFCI-4008	ED-PD-TW-GFCI-8024
GFCI Class	Class A GFCI, 4-6mA Trip Level	Class A GFCI, 4-6mA Trip Level	Class A GFCI, 4-6mA Trip Level	Class A GFCI, 4-6mA Trip Level
Neutral Protection	Open, grounded	Open, grounded	Open, grounded	Open, grounded
Operating Temp.	-31°F to 150°F (-35°C to +66°C)	-31°F to 150°F (-35°C to +66°C)	-31°F to 150°F (-35°C to +66°C)	-31°F to 150°F (-35°C to +66°C)
Nema Rating	NEMA 5-15 P&R	NEMA 5-15 P&R	NEMA 5-15 P&R	NEMA 5-15 P&R
Voltage	Rating 125V AC 60Hz 15A	Rating 125V AC 60Hz 15A, 1875W	Rating 125V AC 60Hz 15A, 1875W	Rating 125V AC 60Hz 15A, 1875W
Surge Suppressor	13 Joules	160 Joules	13 Joules	160 Joules
Insulation Voltage	1500 V RMS 1min.	1500 V RMS 1min.	1500 V RMS 1min.	1500 V RMS 1min.
Weather Rating	-	Rainproof rated	Rainproof rated	Rainproof rated
Certifications	UL listed, CSA certified	UL listed, CSA certified	UL listed, CSA certified	UL listed, CSA certified
Patent	U.S. Pat. No. 5757598	U.S. Pat. No. 5757598	U.S. Pat. No. 5757598	U.S. Pat. No. 5757598
	U.S. and foreign patents pending	U.S. and foreign patents pending	U.S. and foreign patents pending	U.S. and foreign patents pending