



Quality Products. Service Excellence.

## Multi-Mount Wall-Mount Rack Cabinet *SDC Series*

Secure, enclosed cabinet with flexible mounting options for IT, telecom, and edge network deployments.

### Key Features and Benefits



- 16-gauge steel cabinet (frame, cover, doors) with 12-gauge rails; **static load ratings:** up to 150 lb wall or ceiling mounted, and 800 lb freestanding; provides durable, high-strength support with integrated rack unit markings.
- Configurable enclosure with optional doors and panels: choose vented doors for improved airflow or solid options for added protection based on application needs.
- Accessory panel with multiple conduit knockouts: supports 2.5", 2.0", 1-3/8", 1-3/4", 1-1/8", and 7/8" knockouts for flexible cable entry and installation.
- Fan-ready design: includes knockouts for optional fan kits to support active cooling when required.
- Secure, space-efficient wall-mount design (19" rack compatible): protects equipment while maximizing usable wall space in tight environments.
- TAA-compliant, RoHS compliant, manufactured in North America: meets government and environmental standards with consistent quality and supply reliability.
- Black powder coat finish (GREENGUARD Gold, TSCA, and RoHS compliant) provides a low-emitting, corrosion-resistant finish suitable for indoor environments.



The SDC Series wall-mount cabinet is designed for securely housing 19-inch rack equipment in space-constrained environments where protection, organization, and accessibility are required. It provides a compact enclosure for network and IT equipment while maintaining a professional, secure installation.

### Where the SDC Works Best

- Small network closets and IT rooms.
- Retail and branch locations.
- Telecom and low-voltage installations.
- Office environments requiring secure equipment storage.
- Edge and distributed network deployments.

### Applications and when to use the SDC Series

- Equipment needs to be secured with a lockable enclosure.
- You want protection from dust and tampering.
- Floor space is limited.
- A clean, organized installation is required.

### When an Open Rack May Be a Better Choice

Consider alternatives (VPB or RB-CW) when:

- Maximum airflow and access are priorities.
- Budget is the primary concern.
- Security and enclosure are not required.

### Gallery



### Accessories

- Rack Panels for Rack Optimization
- Universal Rack Shelf Fixed Steel (Up to 200 lb Capacity)
- RMU Label Kit (Set of 2)
- We Manufacture PDUs and Outlet Strips
- Ground Stud Kit
- Magnet Panel Cover
- Heavy Duty Cooling Fan Kits
- 10-32 Mounting Hardware
- Rack and Cabinet Caster Set

| Part No.    | Overall Dimensions |       |       | Rack Units | Mounting (Usable) Dimensions |       |       |
|-------------|--------------------|-------|-------|------------|------------------------------|-------|-------|
|             | Height             | Width | Depth |            | Height                       | Width | Depth |
| SDC243U17BK | 7.47               | 24.00 | 17.50 | 3U         | 5.25                         | 19.00 | 15.50 |
| SDC243U24BK | 7.47               | 24.00 | 24.50 | 3U         | 5.25                         | 19.00 | 22.50 |
| SDC243U31BK | 7.47               | 24.00 | 31.50 | 3U         | 5.25                         | 19.00 | 29.50 |
| SDC243U36BK | 7.47               | 24.00 | 36.00 | 3U         | 5.25                         | 19.00 | 34.00 |
| SDC246U17BK | 12.72              | 24.00 | 17.50 | 6U         | 10.50                        | 19.00 | 15.50 |
| SDC246U24BK | 12.72              | 24.00 | 24.50 | 6U         | 10.50                        | 19.00 | 22.50 |
| SDC246U31BK | 12.72              | 24.00 | 31.50 | 6U         | 10.50                        | 19.00 | 29.50 |
| SDC246U36BK | 12.72              | 24.00 | 36.00 | 6U         | 10.50                        | 19.00 | 34.00 |
| SDC249U17BK | 17.97              | 24.00 | 17.50 | 9U         | 15.75                        | 19.00 | 15.50 |
| SDC249U24BK | 17.97              | 24.00 | 24.50 | 9U         | 15.75                        | 19.00 | 22.50 |
| SDC249U31BK | 17.97              | 24.00 | 31.50 | 9U         | 15.75                        | 19.00 | 29.50 |
| SDC249U36BK | 17.97              | 24.00 | 36.00 | 9U         | 15.75                        | 19.00 | 34.00 |

### Optional Accessories

| Cabinet Rack Units | Solid Locking Door | Vented Locking Door | Cable Entry/ Fan Locking Door | Conduit/ Fan Cover Panel |
|--------------------|--------------------|---------------------|-------------------------------|--------------------------|
| 3U                 | SDC3UD             | SDC3UVD             | SDC3USD                       | SDC3UCFP                 |
| 6U                 | SDC6UD             | SDC6UVD             | SDC6USD                       | SDC6UCFP                 |
| 9U                 | SDC9UD             | SDC9UVD             | SDC9USD                       | SDC9UCFP                 |

### Optional Caster Kit

| Part No.   | Strength    | Style/ Material    | Overall Height |                  | Hole Mounting Pattern |       | Caster Set Weight Capacity | Qty Included In Set | Qty with Brakes Included |
|------------|-------------|--------------------|----------------|------------------|-----------------------|-------|----------------------------|---------------------|--------------------------|
|            |             |                    | Wheel Diameter | Added to Cabinet | Width                 | Depth |                            |                     |                          |
| 1425BLSOFT | Light Duty  | Soft Thermoplastic | 2.95           | 3.50             | 1.75                  | 3.00  | 660 lbs (299 kg)           | 4                   | 4                        |
| 1425BM     | Medium Duty | Hard Composition   | 3.00           | 3.81             | 1.75                  | 3.00  | 700 lbs (318 kg)           | 4                   | 0                        |
| 1425BH     | Heavy Duty  | Hard Composition   | 3.00           | 3.81             | 1.75                  | 3.00  | 1,050 lbs (476 kg)         | 4                   | 0                        |
| 1425BHLOCK | Heavy Duty  | Hard Composition   | 3.00           | 3.81             | 1.75                  | 3.00  | 1,050 lbs (476 kg)         | 4                   | 4                        |

| Qty Included | Description                    | Replacement Part No. |
|--------------|--------------------------------|----------------------|
| 1            | Enclosure with installed cover |                      |
| 10           | 10-32 screws and cage nuts     | <b>CAGKIT1032-10</b> |
| 1            | Installation instructions      |                      |

Data subject to change without notice

Tags: **Wall Mount, Server, Ceiling Rack, Under Desk, Side-Mount Rack, Security Lock Box, Louver, Slim Wall Enclosure, Wall-Mount Serve Rack**

© 2026. Hammond Manufacturing Ltd. All rights reserved.