

Steel Sealtite Fittings

Construction

- Zinc plated steel fitting, has a five piece construction consisting of a gland nut, sealing ring, high tensile grounding ferrule, insulated throat, and body.
- Included sealing ring and galvanized steel lock nut provides a means for connecting the fitting to boxes.
- Corrosion resistant, protects from moisture and oils.

Installation

Fitting is ideal for use with standard liquid-tight conduit to allow easy installation. IP 66/67 Rated when installed with approved





1 2

<u>ltem #</u>	Connector Type	<u>Type</u>	Electrical Trade Size	Dimension A	Dimension B	Dimension C	K.O. Size	Thread Type
<u>7STR600B</u>	Straight	Zinc Plated Steel	6 in	6.00 in	N/A	N/A	6 in	NPT
7STR25045B	45°	Zinc Plated	2-1/2 in	4.75 in	1.50 in	4.00 in	2- 1/2	NPT _

Item #	Connector Type	Type	Electrical Trade Size	Dimension A	Dimension B	Dimension C	K.O. Size	Thread Type
		Steel					in	
7STR30045B	45°	Zinc Plated Steel	3.00 in	5.50 in	1.50 in	4.63 in	3 in	NPT
7STR40045B	45°	Zinc Plated Steel	4 in	7.75 in	1.63 in	5.81 in	4 in	NPT
7STR25090B	90°	Zinc Plated Steel	2-1/2 in	8.00 in	1.50 in	N/A	2- 1/2 in	NPT
7STR30090B	90°	Zinc Plated Steel	3.00 in	8.75 in	1.50 in	N/A	3 in	NPT
7STR40090B	90°	Zinc Plated Steel	4 in	12.63 in	1.50 in	N/A	4 in	NPT

1 2